

Securefast SED992

Push Bar Panic Bolt

Certified to EN1125 : 2008

Fire Rated for Timber and Steel Doors

Suitable for Single Doors and the Inactive Leaf (2nd Opening) of Rebated Double Doors

Universal for Left and Right Hand Doors - Handing can be change to suit an Outside Access Device

Adjustable Top and Bottom Shoot bolts, offering + or – 5mm of adjustment

Available with Manual Hold Back (not to be used on Fire Doors unless the door has been fire tested with unlatched hardware)

Anti-thrust device to prevent the shoot bolt from being retracted.

Supplied with an easy clean socket

The Slave unit can be supplied with a Micro Switch for linking to an Access Control System.

Suitable for door 1300mm wide and 2500mm high

Outer Box Quantity - 4

Individual Box Size L124cm x W17.5cm x H7cm

Individual Weight 4.8kg

SED992/SE
Right Hand illustrated



Options

Part No.	Description	Classification Code
SED992/SE	Push Bar Panic Bolt	3 7 6 B 1 4 2 2 A A
SED992/SE/HB	Push Bar Panic Bolt with Hold Back	3 7 6 0 1 4 2 2 A A

Finishes

Powder Coated Silver (SE), Gold (GD), Black (BK)
Nickel Plated Imitated Satin Stainless Steel (SS)

Accessories

SED990/xx/LE Outside Access Device with Lever Handle
SED990/xx/KN Outside Access Device with Knob
SED999/M Micro-Switch Slave Unit - For linking to an Access Control or Monitoring System
Additional Top Shoot (SED999/S), Guide (SED999/G) and Connector (SED999/B) for Extra High Doors
Surface Mounted Top Trip Keep available for Steel and Timber frames.