

The EXS Light is a large general purpose, emergency escape route sign suitable for all interior applications. The maximum viewing distance is 60 meters. Comprising of a white stove enamelled, zintec coated sheet steel base fitted with a self extinguishing legend panel, suitable for use on escape routes (850 degree C Hot-wire test, defined by ICEL). The EXS Light has cable knockouts, which are provided in the sides and the top with a BESA entry in the back. Complying with the requirements of EN60598-2-22 and suitable for incorporation into an emergency lighting system complying with BS5266-1:2005. The EXS Light can be fitted with legends complying with the Health and Safety signs directive of 1996, while for extensions a full range of BS5499 legends remain available. With flexibility in mind a full range of alternative finishes are available including any British Standard or RAL colour, brass and chrome.



Pictured with standard exit box ES8M in foreground

- IP20 Interior Use
- Escape Route Sign
- Downlight Facility
- Choice of Legend
- Can be Ceiling Mounted
- Colour Options Available
- Brass/Chrome Version
- Central Battery Versions
- Self-Contained
- Centrally Supplied

TYPICAL APPLICATIONS

- High Bay Warehouses
- Large factories
- Inside Final Exit
- Sports Stadiums
- Super Markets/Shopping complexes
- Airports

	Mode	Lamp Type	Power Con	Battery	Duration	Weight	Emerg Output	Dimensions
EXS18NM	Non Maintained	18W T8	9 VA	3.6V 4Ah	3 Hours	4 Kg	200 Lumens	620 x 310 x 100
EXS18M	Maintained	18W T8	38 VA	3.6V 4Ah	3 Hours	4.75 Kg	200 Lumens	
EXS18/SL/*	Mains or Slave	18W T8	8 - 38 VA			3.5 - 4 Kg	200 Lumens	

* Please suffix voltage required i.e. 24, 50, 110, 230

Suffix part number with

/L	-	Left Arrow
/R	-	Right Arrow
/BR	-	Brass finish
/CR	-	Chrome finish
/ST	-	Self Test

NOTE: All exit signs arrow down as standard if other direction is required please specify