

The TPX Light is an attractive low profile, versatile emergency luminaire suitable for internal and sheltered external environments and with the added advantage of being able to take a self-adhesive escape route legend. Comprising of a moulded polycarbonate base and fitted with a clear flame-retardant diffuser, suitable for use on escape routes. The diffuser is screw fixed to the base and provides a seal up to IP55. The TPX also offers an edge-lit exit sign version which has a viewing distance of 32 meters (IP20 with sign). The hinged gear tray is easily removable to allow first fix of the base. Cable knockouts are provided in the ends and a BESA entry in the base. Complying with the requirements of EN60598-2-22 and suitable for incorporation into an emergency lighting system complying with BS5266-1:2005. Available in white.

TYPICAL APPLICATIONS

- Corridors
- Exit routes
- Office complexes
- Night Clubs
- Areas of aesthetic importance

- IP55 / (IP20 with edge-lit sign)
- Polycarbonate base
- Clear Diffuser
- High Light Output Versions
- 8w T5 Lamp
- Self-Contained
- Centrally Supplied
- Universal legend kit and Edge-lit Exit sign options



	Mode	Lamp Type	Power Con	Battery	Duration	Weight	Emerg Output Lumens	Dimensions
TPX8NM	Non Maintained	8W T5	8 VA	2.4V 4Ah	3 Hours	1.8 Kg	100 Lumens	355 x 195 x 70
TPX8M	Maintained	8W T5	20 VA	2.4V 4Ah	3 Hours	2.0 Kg	100 Lumens	
TPX8S	Sustained (Combined)	8W T5 (two of)	20 VA	2.4V 4Ah	3 Hours	2.0 Kg	100 Lumens	
TPX8/SL/*	Mains or Slave	8W T5	7 - 20 VA			1.1 - 1.35 Kg	270 Lumens	

* Please suffix voltage required i.e. 24, 50, 110, 230

Suffix part number with
 /RS - Recessed Version
 /EX - Edge-lit Exit sign Version
 /ST - Self Test

NOTE: All exit signs arrow down as standard if other direction is required please specify

