



Text Messaging Smoke Alarm

DC operated, photoelectric smoke alarm with integrated GSM module.

MODEL: S588-ELS



- DC Operated, Photoelectric type Smoke alarm with integrated GSM module.
- Photoelectric sensor for detection of smouldering fires
- Insect proof
- TEST button
- High and stable sensitivity
- Quick-fix mounting plate for easy installation.
- Battery missing fixing lock feature
LED indicator
- Extra loud audible alarm in excess of 85dB
- Low battery and battery missing warning indicator.
Auto-reset when smoke clears
- Smoke detection complies with CE, BSI, SAI Global approved and with EN14604, AS3786 and UL217 standard.

Technical Specifications

Model	S588-ELS
Detection Type	Photoelectric
Operation Temperature	5deg - 45deg
Power Source	9V Lithium battery
Standby current	15uA Max
Alarm current	30mA Max
Connection type	SIM Card
Antenna reception	Max -67dBm; Range -73dBm - -67dBm
Alarm sound	85 decibels at 3m
Ambient humidity	10% - 90%
Sensitive to Smoke	3.0 – 6.0 %Obs/m
Product Weight	201g (including battery)
Product Dimensions	115 x 47mm

Shipping Details

Unit Dimensions	145 x 145 x 65mm
Minimum order Qty	100



Copyright ©2011 ELS.

ELS are registered in England and Wales 6847881