

The 790MRL heat alarm is mains powered with rechargeable battery back up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix). The PUSH-FIT base provides spacious room for wiring in premises such as flats where concrete ceilings can be problematic. Top and side entries accommodate for either cable or mini trunking installations.



Product features:

- 230V mains powered heat alarm
- Rechargeable lithium battery back up
- PUSH-FIT docking base
- Advanced class A2 thermistor sensor
- Test/ hush button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke & heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS 5446-2: 2003

Model number	790MRL
Description	230V heat alarm with PUSH-FIT docking base
Technology	Advanced class A2 thermistor sensing technology
Sensitivity	N/A
Alarm sound level	85db at 3m
Battery type	Rechargeable lithium battery back up
Operation AC/DC	AC
Installation positions	Ceiling
Operating temperature	+5°C to +38°C
Operating humidity	10% to 85% relative
Storage temperature	+5°C to +38°C
Storage humidity	10% to 85% relative
Warranty	5 years

Dimensions	140mm (diameter) x 68mm (depth)
Unit weight	301g
Pack dimensions	141mm (H) x 141mm (W) x 83mm (D)
Pack weight	303g
Master pack quantity	10
Master pack dimensions	312mm (H) x 396mm (W) x 153mm (D)
Master pack weight	3.04kg
Pack barcode	00029054019844
Outer barcode	10029054019841
Approvals	BS 5446-2: 2003