

The ES Light is a general purpose, cost effective emergency escape route sign suitable for all interior applications. Comprising of a white stove enamelled, zintec coated sheet steel base fitted with a self extinguishing legend panel, suitable for use on escape routes (850 degree C Hot-wire test, defined by ICEL). The ES Light has cable knockouts, which are provided in the sides and the top with a BESA entry in the back. Complying with the requirements of EN60598-2-22 and suitable for incorporation into an emergency lighting system complying with BS5266-1:2005. The ES Light can be fitted with legends complying with the Health and Safety signs directive of 1996, while for extensions a full range of BS5499 legends remain available. With flexibility in mind a full range of alternative finishes are available including any British Standard or RAL colour, brass and chrome.



- IP20 Interior Use
- Escape Route Sign
- Downlight Facility
- Choice of Legend
- Can be Ceiling Mounted
- Colour Options Available
- Brass/Chrome Version
- Central Battery Versions
- Self-Contained
- Centrally Supplied

TYPICAL APPLICATIONS

- Student Accommodation
- Offices/Factories
- Hotels/Public Houses
- High Bay Warehouses
- Shops/Shopping complexes
- Inside Final Exit

■ Sports Halls

IP65 Exit Box



Available

	Mode	Lamp Type	Power Con	Battery	Duration	Weight	Emerg Output	Dimensions
ES8NM	Non Maintained	8W T5	8 VA	2.4V 4Ah	3 Hours	1.4 Kg	100 Lumens	380 x 190 x 60
ES8M	Maintained	8W T5	20 VA	2.4V 4Ah	3 Hours	1.75 Kg	100 Lumens	
ES8/SL/*	Mains or Slave	8W T5	7 - 20 VA			1.2 - 1.5 Kg	270 Lumens	
ESW8M	Maintained	8W T5	8 VA	2.4V 4Ah	3 Hours	IP65 Exit box		

* Please suffix voltage required i.e. 24, 50, 110, 230

Suffix part number with

- /L - Left Arrow
- /R - Right Arrow
- /BR - Brass finish
- /CR - Chrome finish
- /ST - Self Test

NOTE: All exit signs arrow down as standard if other direction is required please specify

