

## **ST-750T** THERMOPTEK® SMOKE ALARM

Sensor type	Thermoptek Multi-Sensor
Battery type	10 year sealed for life lithium





- Thermoptek Multi-Sensor technology as used by over 90% of the UK Fire and Rescue Services.
- 10 year sealed for life **Panasonic** battery, removes the need to replace the battery.
- Large central button Test / Smart Silence.
- Easy to install with automatic battery engagement on base plate.
- Smart Silence allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm.
  During these 10 minutes if additional smoke is detected the alarm will sound.
- Sleep Easy allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.







## **Technical Specification**

Dimensions	130mm (diameter) x 34mm (depth)
Supply voltage	3V DC
Battery	10 year sealed for life <b>Panasonic</b> battery
Technology	Thermoptek
Alarm sound level	85dB(A) at 3m (minimum)
Installation positions	Ceiling / Wall
Operating temperature	+4°C to +38°C
Operating humidity	Up to 90% RH non-condensing
Storage temperature	-20°C to +60°C
Storage humidity	Up to 93% RH non-condensing
Plastic material	ABS, UL94 VO fire retardant
Warranty	10 years
Weight	155g
Certified to	BS EN 14604: 2005 +AC:2008
Barcode	0816317004064