

FireAngel[®] Pro CONNECTED

FP1014W2-R BATTERY POWERED WIRELESS INTERLINK ALARM CONTROL UNIT

Battery type

Replaceable battery (10 Year product life)



- Connects to FireAngel Connect Gateway
- Separate fire and CO alarm indicators
- A remote interface for up to 50 **Wi-Safe 2** units
- Test function - allows you to test all interlinked alarms from one centralised location
- Silence function - silence all interlinked smoke and heat alarms. An alarm cannot be silenced if CO has been detected, however the locate function allows the initiating CO alarm to be located
- Locate function - silence all wirelessly interlinked alarms except the initiating alarm
- AA alkaline battery - 3 year battery life
- Memory function - if one of the alarm indicators is flashing every 10 seconds a smoke, heat or CO alarm has been activated

Technical Specification

Dimensions	90mm (width) x 90mm (height) x 22.5mm (depth)
Supply voltage	3VDC
Battery	Replaceable battery
Installation positions	Wall / Portable
Technology	Wi-Safe 2
Operating temperature	+4°C to +38°C
Operating humidity	Up to 90% RH non-condensing
Storage temperature	-20°C to +60°C
Storage humidity	Up to 93% RH non-condensing
Plastic material	ABS, UL94 VO fire retardant
Warranty	5 years
Weight	142g
Certified to	N/A
Independently tested to	ETSI EN 300 220-2 V2.4.1, ETSI EN 301 489-1 V1.9.2, ETSI EN 301 489-3 V1.6.1
Maximum number of connected units	50 wireless units
Operating Frequency	868 MHz
Range	35m (over 200m in clear air)



FireAngel Connect

Monitor and manage multiple devices wherever you are with FireAngel Connect



Heat Alarm



Smoke Alarm



Control Unit



CO Alarm