

RF-link Hard of Hearing System

MODEL		WARRANTY
FHN800HIA	Mains powered with rechargeable battery back-up	10 YEARS

- **RF-LINK** Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA)
- **Mains Powered Control Unit with Rechargeable Battery Back up.**
The Control Unit has a high intensity LED Flashing Strobe light to alert the user that an alarm has been activated
- **Vibrating pillow pad**
placed under a pillow will vibrate to alert the user when in bed



TECHNICAL SPECIFICATION	
Power Supply	Mains powered with rechargeable battery back-up
Alarm Type	Vibrating Pad & Strobe Light
Alarm interlink (RF-Link)	Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA)
Indicators	GREEN LED (mains power), RED LED (FIRE and CO Alarm) , YELLOW LED (Fault).
Device Fixing	Table Stand or Wall Mount.
Test/Hush	Test & Silence
Dimensions	75mm x 75mm x 35mm
Weight	0.514 kg
Use in:	Dwelling houses, Caravans/motorhomes & Leisure vehicles, Boats.
Installation positions	Control unit can be free standing or wall mounted
Operating Temperature	-10°C or greater +40°C
Operating Humidity	30% - 90% RH
IP Rating	IP42
Packaging	Individual box & Outer carton (Recyclable cardboard)
Master pack/Outer carton	10 units
Maximum interlinked alarms	20 x RF-LINK alarms (Maximum of 15 if used with FHN800HIA)
Barcode	EAN - 5055278500993
Approval/Certified to	Conforms to BS5446-3: 2015
Warranty	10 years