

Product data sheet

Closer body TS 1000 C

*



Basic body for overhead door closer with link arm EN 2/3

AREAS OF APPLICATION

- Right and left single-action doors for interior use
- Single-action doors up to 950 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side

Closer body TS 1000 C *



PRODUCT FEATURES

- Two different variable closing force settings, which can be selected simply by turning the bearing block for the link arm
- Closing speed can be adjusted from the side via valve
- Latching action can be adjusted from the side via valve
- Door closer, can be used for right and left hand doors

TECHNICAL DATA

Productname	Closer body TS 1000 C *
Closing force in accordance with EN 1154	EN 2/3
Leaf width (max.)	950 mm
Type of installation	Door leaf installation hinge side, Transom installation opposite hinge side
Opening angle (max.)	180 °
Identical design for DIN left and DIN right	Yes
Standard conformity	EN 1154:1996/A1:2002/AC:2006
Suitability for fire protection doors	Yes
Length	215 mm
Width	44 mm
Height	52 mm
Closing force adjustable	Yes, via installation
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	No
Position of closing force adjustment	Mounting position
Smoke switch integrated	No

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.