

Product data sheet

TS 1500 G with hold-open



Overhead door closer with guide rail for up to 750 mm leaf width with mechanical hold-open device

AREAS OF APPLICATION

- Right and left single-action doors
- Single-action doors up to 750 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side

TS 1500 G with hold-open



PRODUCT DESCRIPTION

The overhead door closer TS 1500 G with guide rail is suitable for 1-leaf internal doors up to 750 mm leaf width (fixed closing force EN size 1).

PRODUCT FEATURES

- Fixed closing force of EN1
- Can be used for right and left hand doors without conversion
- Mechanical hold-open unit in the guide rail with hold-open area 80°-130°
- Hydraulic latching action which accelerates the door shortly before it is closed
- Closing speed can be individually adjusted
- All functions can be adjusted from the front

TECHNICAL DATA

Productname	TS 1500 G with hold-open
Leaf width (max.)	750 mm
Type of installation	Door leaf installation hinge side, Transom installation opposite hinge side
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	No
Position of closing force adjustment	At the side
Hold-open function	Mechanical
Smoke switch integrated	No

PART

GUIDE RAIL TS 1500 G/F *

with mechanical hold-open device and lever



TS 1500 G with hold-open



Designation	Description	Ident-No.	Colour	Dimensions	Hold-open point min.
Guide rail TS 1500 G/F *	with mechanical hold-open device and lever	101889	silver-coloured	390 x 30.5 x 20.5 mm	80 °
Guide rail TS 1500 G/F *	with mechanical hold-open device and lever	101892	according to RAL	390 x 30.5 x 20.5 mm	80 °
Guide rail TS 1500 G/F *	with mechanical hold-open device and lever	101891	white RAL 9016	390 x 30.5 x 20.5 mm	80 °

CLOSER BODY TS 1500 G *

Main body for overhead door closer with guide rail EN 1



ACCESSORIES

COVER CAP DOOR CLOSER

For TS 1500, can only be used for door leaf installation



Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer	For TS 1500, can only be used for door leaf installation	080147	silver-coloured	188 x 47 x 57.5 mm
Cover cap door closer	For TS 1500, can only be used for door leaf installation	080149	white RAL 9016	188 x 47 x 57.5 mm
Cover cap door closer *	For TS 1500, can only be used for door leaf installation	080148	dark bronze	188 x 47 x 57.5 mm

FLEXIBLE OPENING RESTRICTOR

For riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail



Designation	Description	Ident-No.	Dimensions	Material
Flexible opening restrictor	For riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail	069780		Plastic

TS 1500 G with hold-open



INSTALLATION MATERIAL

MOUNTING PLATE GUIDE RAIL *

For TS 1500 G



Designation	Description	Ident-No.	Colour	Material
Mounting plate guide rail *	For TS 1500 G	072355	according to RAL	Aluminum
Mounting plate guide rail	For TS 1500 G	072333	silver-coloured	Aluminum

MOUNTING PLATE DOOR CLOSER

For TS 1500



Designation	Description	Ident-No.	Colour	Material
Mounting plate door closer *	For TS 1500	029683	dark bronze	Aluminum
Mounting plate door closer	For TS 1500	029682	silver-coloured	Aluminum
Mounting plate door closer	For TS 1500	029685	white RAL 9016	Aluminum
Mounting plate door closer	For TS 1500	029686	according to RAL	Aluminum

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.