

Product data sheet

Closer body TS 2000

NV BC



Main body for overhead door closer with link arm EN 2-4 with back check

AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 1100 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side
- Door leaf installation opposite hinge side in parallel arm installation possible

Closer body TS 2000 NV BC



PRODUCT FEATURES

- Closing force with variable adjustment from the side
- Closing speed can be adjusted from the front via valve
- Latching action can be adjusted from the front via valve
- Back check can be adjusted from the front via valve
- Door closer, can be used for right and left hand doors
- Door closer, can be used for leaf and transom installation
- Minimal installation effort due to low number of individual parts and quick setting

TECHNICAL DATA

Productname	Closer body TS 2000 NV BC
Closing force in accordance with EN 1154	EN 2 - 4
Leaf width (max.)	1100 mm
Type of installation	Door leaf installation hinge side, Transom installation opposite hinge side, Door leaf installation opposite hinge side
Opening angle (max.)	180 °
Identical design for DIN left and DIN right	Yes
Standard conformity	EN 1154:1996/A1:2002/AC:2006
Suitability for fire protection doors	Yes
Length	226 mm
Width	51 mm
Height	60 mm
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	Yes, hydraulically adjustable
Position of closing force adjustment	At the side
Thermo-control valves	Yes
Integrated smoke switch	No

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 2000 NV BC Closer	Closing force EN2-4 with back check (without link arm)	124944	silver-coloured	EN 2 - 4	226 x 51 x 60 mm
GEZE TS 2000 NV BC Closer	Closing force EN2-4 with back check (without link arm)	124947	according to RAL	EN 2 - 4	226 x 51 x 60 mm
GEZE TS 2000 NV BC Closer	Closing force EN2-4 with back check (without link arm)	124945	dark bronze	EN 2 - 4	226 x 51 x 60 mm

Closer body TS 2000 NV BC



Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 2000 NV BC Closer	Closing force EN2-4 with back check (without link arm)	124946	white RAL 9016	EN 2 - 4	226 x 51 x 60 mm
GEZE TS 2000 NV BC Closer	Closing force EN2-4 with back check (without link arm)	205332	black RAL 9005	EN 2 - 4	226 x 51 x 60 mm

INSTALLATION MATERIAL

MOUNTING PLATE SEGMENTAL ARCHED DOOR *

for TS 2000 NV, arch height max. 130 mm



Designation	Description	Ident-No.	Colour
Mounting plate segmental arched door *	for TS 2000 NV, arch height max. 130 mm	127434	silver-coloured
Mounting plate segmental arched door	for TS 2000 NV, arch height max. 130 mm	127435	according to RAL

GLASS CLAMPING SHOE

For TS 3000 / 2000 NV



Designation	Description	Ident-No.	Colour	Glass thickness
Glass clamping shoe	for TS 3000/TS 2000 NV	014835	silver-coloured	10 mm
Glass clamping shoe	for TS 3000/TS 2000 NV	014843	white RAL 9016	10 mm
Glass clamping shoe	for TS 3000/TS 2000 NV	014836	dark bronze	10 mm
Glass clamping shoe	for TS 3000/TS 2000 NV	014845	according to RAL	10 mm

Closer body TS 2000 NV BC



MOUNTING PLATE AND COUNTERPLATE ALL-GLASS DOOR

For TS 3000 / 2000 NV



Designation	Description	Ident-No.	Colour	Glass thickness
Mounting plate and counterplate all-glass door	for TS 3000/TS 2000 NV	090259	silver-coloured	10 mm

MOUNTING PLATE DOOR CLOSER

For TS 2000 NV (BC) with hole pattern in accordance with DIN EN 1154 Supplement 2



Designation	Description	Ident-No.
Mounting plate door closer	for TS 2000 NV and NV BC with hole pattern according to DIN EN 1154 Supplement 1	126234

LINTEL CASING BRACKET

For TS 3000 / 2000 NV



Designation	Description	Ident-No.	Colour
Lintel casing bracket	for TS 2000 NV / TS 3000 V	127433	according to RAL
Lintel casing bracket	for TS 2000 NV / TS 3000 V	127432	silver-coloured

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.