

 <p><b>JALITE</b><sup>®</sup> Photoluminescent Safety Products</p>	<p><b>JALITE PLC</b> Wins House, Bentalls Pipps Hill Industrial Estate Basildon, Essex, SS14 3BS, UK Tel: (44) 0 1268 242300 Fax: (44) 0 1268 274148 Email: sales@jalite.com</p>	<p><b>JALITE USA</b> 190 Old Milford Milford, PA 18337 USA Tel: (1) 570 296 6906 Fax: (1) 570 296 5656 Email: sales@jaliteusa.com</p>	<p><b>JALITE ASIA</b> 528 Ocean Centre 5 Canton Road, Tsimshatsui Kowloon, Hong Kong Tel: (852) 3426 9266 Fax: (852) 3528 0757 Email: sales@jalite-asia.com</p>
---	--	---	---

**Maintaining Your Jalite Product:**

Jalite AAA Rigid PVC material has a long service life provided it is correctly maintained. Products should be periodically cleaned at two month intervals, cleaning intervals may need to be increased to compensate for harsh operating environments. It is important to use a non aggressive cleaning method as aggressive cleaning will scratch the printed surface. It is recommended that a soft cloth and a mild cleaning agent are used with a gentle cleaning action. This will remove any residue dirt, dust or grease present which impedes the Jalite AAA light transmission.

It is of the up most importance that NO solvent or chemical cleaning products are used as this will attack the printed surface of the sign.

Provided these maintenance guidelines are followed your Jalite product will provide you with many trouble free years of service.

We hope you are extremely satisfied with your Jalite product.

**Recommended Fixing Methods:**

**Mechanical Fixing:** - Jalite AAA Rigid signs can be easily drilled to accommodate various screw sizes; generally 4 fixings per sign are used.

**Adhesive bonding:** - Various bonding materials are available on the market today but Jalite have used two main solvent free methods for many years now and these are silicon and adhesive tape.

**Silicon:** - Using a conventional solvent free silicon adhesive and application gun ‘zig zag’ beads are run on the reverse of the sign which is then placed in its desired location, the adhesive has a high initial grab which holds the sign in place whilst full curing occurs. Silicon adhesives are of particular use when applying to a surface with slight imperfections and undulations as the silicon spreads to accommodate various surface types.

**Double sided Adhesives:** - The selection of adhesive tape is based purely upon the application surface. Flat surfaces i.e. smooth painted plasterboard finishes a thin carrier adhesive type would be used, where as a textured surface would require a foam type adhesive to cater for imperfections and undulations in the surface. Jalite can supply Jalite AAA rigid signs with adhesive pre applied to your particular requirements.

