



Section 1

FIRE FIGHTING EQUIPMENT

FirePower

WATER EXTINGUISHERS WITH ADDITIVE - Stored Pressure

- Kitemarked to BS EN3
- Special additive gives improved fire ratings
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base
- Complete with wall bracket
- Have passed the 35kv conductivity discharge test



Type	WATER ADDITIVE SP	WATER ADDITIVE SP
Capacity (ltr)	3	6
Fire Rating	13A	21A
Height (mm)	426	560
Cylinder Dia (mm)	130	150
Overall Width (mm)	280	280
Filled Weight (kg)	5.6	9.52
Range of Throw (m)	>3	>3
Duration of Discharge (secs)	25	60
Working Pressure (at 20 °C)	15	15
Temperature Range (°C)	+5 to +60°C	+5 to +60°C
BS EN3 Approved	✓	✓
Med Approved	NO	NO
Part Number	9911/00	9912/00
Model Number	FPRWA3	FPRWA6
Rating Symbol	A	A



FirePower

WATER EXTINGUISHERS - Stored Pressure/Cartridge Operated

- Kitemarked to BS EN3
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base
- Complete with wall bracket
- 6ltr has passed the 35kv conductivity discharge test



Type	WATER C/O	WATER SP	WATER SPRAY SP
Capacity (ltr)	9	9	6
Fire Rating	21A	21A	13A
Height (mm)	620	522	560
Cylinder Dia (mm)	190	190	150
Overall Width (mm)	290	320	280
Filled Weight (kg)	14.9	13.29	9.52
Range of Throw (m)	>10	>10	>3
Duration of Discharge (secs)	60	60	50
Working Pressure (at 20 °C)	15	15	15
Temperature Range (°C)	+5 to +60°C	+5 to +60°C	+5 to +60°C
BS EN3 Approved	✓	✓	✓
Med Approved	✓	✓	NO
Part Number	9908/00	9909/00	9910/00
Model Number	FPRW9C	FPRW9	FPRWS6
Rating Symbol	A	A	A

