

Heat Alarm

10 YEAR LITHIUM CELL POWERED

RadioLINK® Interconnectivity

Model Ei 603TYCRF HEAT Alarm

- Practically eliminates false alarms
- Suitable for Kitchens & areas where smoke alarms may be subjected to false alarms.
- RadioLINK Interconnectivity – one alarm sounds all alarms in system
- Aesthetically pleasing, compact design
- Battery capacity is sufficient to outlast the useful lifespan of the alarm.
- Large Easy to use Test button
- Easy to fit twist-on base
- Kitemarked to BS 5446-2:2003
- Manufactured in Ireland to ISO 9001:2000



Product Description

The Ei603TYCRF alarm is activated by heat from a fire, not smoke, which makes it ideal for kitchen installations where smoke detectors are prone to nuisance alarms.

The Ei603TYCRF has a 10 Year Lithium battery that is non replaceable.

The Ei603TYCRF is interconnected to other smoke / heat alarms in the dwelling or escape routes to ensure that all occupants are alerted to the danger.

Up to 12 battery powered smoke and heat alarms may be linked using hardwire or RF connectivity.

RadioLINK enabled smoke and/or heat alarms can be house coded as a system to prevent communication with other nearby RadioLINK systems.

Operation

- The heat detector will alarm when the temperature reaches 58°C. It will automatically reset and silence the alarm when the temperature drops below this limit.
- The red indicating LED will flash once every 40 seconds to show that the alarm is powered and it has performed an automatic power supply test..
- The built in sounder will provide a minimum sound output of 85dB(A) @ 3m.
- Pressing and holding the "Test" button will check the sensor, electronics and sound the horn.
- The alarm is not powered until it is twisted on the mounting base, thus avoiding battery power consumption during storage and prior to installation.
- The Ei603TYCRF heat alarms and other RadioLINK smoke alarms must be house coded. This will avoid interference and interconnection with other RadioLINK systems.
- Keep all doors closed to rooms with heat alarms at night and while premises are unoccupied.



Shannon Free Zone, Shannon, Co. Clare, Ireland.
Ph.+353 61 471277 Fx.+353 61 471053
Email. eielectronics@eilttd.ie
Web: www.eielectronics.com

Model Ei603TYCRF HEAT Alarm

Technical Specification

| | | | |
|----------------------------|---|--|---|
| Sensor: | Fast response thermistor (class A1) with threshold set to 58°C | Alarm: | Piezoelectric-horn |
| Button Test: | Pressing the test button tests the sensor, electronics and horn. | Alarm Sound Output: | 85dB (A) (minimum) @ 3m |
| Battery Voltage: | 9V supplied by 10 Year Lithium Battery with 2,000mAh capacity. | Normal Operating Temperature Range: | 0 to 40°C |
| Power-On Indicator: | Red LED flashes through cover every 40 seconds | Humidity Range: | 15% to 95% Relative Humidity (non-condensing) |
| Alarm Indicator: | Red LED flashes rapidly on the alarm sensing the fire and the sounder is activated. The sounders on all interconnected alarms are also activated. | Hardwire Interconnect: | Interconnect up to 12 alarms and remote control devices |
| | | RadioLINK Interconnect: | Interconnect for up to 12 battery powered RadioLINK alarms and remote control devices |
| | | Fixing: | Screw fixings supplied |
| | | Dimensions: | 115mm (diameter) x 55mm (height) |
| | | Weight: | 200 grams |
| | | Warranty: | 5 year (limited) warranty |
| | | Compliance: | Kitemark to BS 5446-2:2003 , CE approved, Manufactured to ISO 9001:2000 quality standards. |