Technical specs

HA544J_ - HA544J - ABYSSIN

Name:

2 ATTACHMENT PTS HIGH VISIBILITY FALL ARREST FULL BODY HARNESS - EXPERT RANGE

<u>Size:</u>

M - L - XL

<u>Colour:</u>

Fluorescent Yellow



Description:

Indissociable fall arrest full body harness, Expert range, including a fall arrest harness and a high visibility yellow vest. *HA044 fall arrest harness with bicoloured polyester straps (45 mm): 2 attachment points (rear - chest), 1 karabiner, sit strap and quick buckles at thighs level.

*Polycotton vest with Teflon® and waterproof treatment closed by zip including: 2 low pockets with flap, one for mobile-phone, 2 lateral pockets and a mesh lining. Adjustable size with zip (3 in 1).

Materials:

Straps : polyester Vest: Polyester cotton

Instructions for use:

High visibility jacket harness to be clearly seen by day and by night in headlamps and outside in all weathers. This harness is recommended for linesmen and any worker likely to carry out height intrerventions: poles, cranes or other structures, and for sites visitors (inspectors). A harness must be strapped to the body as tight as possible but not excessively to allow total freedom of movements to the user.

This jacket harness must be attached to a chosen anchorage point above the user with a strength greater than or equal to 10kN. Check that the headroom is sufficient and that the general arrangement of the system does not permit pendulum motion in the event of a fall.

There is a dorsal attachment point and a chest attachment point (formed by 2 strap loops jointed by a connector).

Limits to use:

Not to be used for protection against further hazards than defined above. After a fall and every 12 months, return the harness for inspection to the manufacturer or one of his qualified representatives. There are to be no add-ons that might reduce its visible area. This garment contains no known carcinogenic or toxic substances, or substances which may cause allergies in sensitive people.

Instructions for storage:

This jacket harness must be stored away from sunlight, heat and chemical products, in its original packaging.



DELTA PLUS GROUP La Peyrolière - B.P. 140 - 84405 APT Cedex - France www.deltaplus.fr



Technical specs

HA544J_ - HA544J - ABYSSIN

Instructions for cleaning / maintenance:

Wash by hand using household soap (maximum 10 cycles), do not machine wash, washing temperature 30°C maximum, handle with great care, do not wash under running water. No chlorination permitted. Do not iron. Steam treatment is expressly prohibited. Do not dry clean, do not use spot removing solvents. Do not dry in a spin drier, leave to dry in the open air away from any heat source. Do not pre-soak. Do not use high alkalinity detergents based on solvents, or micro emulsion, or bleaching agent.

The equipment must always be inspected before use. Check especially:

- Straps : no start of cutting, of burning, of rusting, of abnormal narrowing.
- Sewing : no visible damage
- Metallic elements : no distortion or oxidation.

If there is any doubt, replace the jacket harness.

Performances :

This high visibility full body harness complies with the European directive 89/686 notably for ergonomics, harmlessness, comfort, airing, flexibility, with EN361 for the harness and EN471-1994 for the jacket.

EN471:1994

High visibility warning clothes



2 : Classify Surface of the Matter (1 to 3)2 : Classify Reflective Matter (1 to 2)



DELTA PLUS GROUP

La Peyrolière - B.P. 140 - 84405 APT Cedex - France www.deltaplus.fr

