

# 8 WATT LOW PROFILE BULKHEAD

The TP Light is a low profile, versatile emergency luminaire for interior applications.

Comprising a moulded, self-extinguishing polycarbonate base and fitted with a clear prismatic diffuser, the TP Light is designed for use on escape routes. It passes the 850°C hot-wire test, as defined by ICEL. The diffuser is clipped to the base to provide a seal to IP40. The gear tray is easily removable to allow first fix of the base. Cable entry is provided in the ends and a BESA entry in the base. The TP Light complies with the requirements of EN60598-2-22 and is suitable for incorporation into an emergency lighting system complying with BS5266-1:2011. White with clear prismatic diffuser as standard, opal diffuser available. Switchable, Maintained and Non-Maintained versions available.



	Lamp Type	Power Con	Battery	Duration	Weight	Emerg Output
TP8M	8W T5	20 W	2.4V 4Ah	3 Hours	1.95Kg	100 Lumens
TP8NM	8W T5	8 W	2.4V 4Ah	3 Hours	1.78Kg	100 Lumens
TP/230/HF	Mains only / Static inverter					
TP/SL/*	ACDC Slave. * suffix voltage required with 24, 50, 110,					
TP8S	Sustained					

Options	
/BK	Black base
/TS	Test switch
/ST	Self Test
/HT	40° ambient
/DALI	DALI
/180	High Emergency output

- IP40 Interior Use
- Slim Profile
- Polycarbonate Base
- Clear Diffuser
- Removable Gear Tray
- Recessing Option
- Self-Contained

