

# ANTI LIGATURE CIRCULAR

www.ringtail.co.uk - +44 (0) 1772 336335 - sales@ringtail.co.uk

**Ringtail**  
Lighting



The SR Light is a circular anti ligature vandal resistant luminaire suitable for interior environments. The SR Light offers a cost-effective emergency lighting and mains lighting combination, and is ideal for areas where higher light levels are required.

- Comprising of white spun aluminium housing.
- Polycarbonate opal diffuser.
- Diffuser is held in place by a security screw fixed rim, fitting flush to the ceiling.
- IP40 ingress protection.
- Suitable for use on escape routes.
- Designed in accordance with the requirements of EN60598-2-22.
- Suitable for incorporation into an emergency lighting system complying with BS5266-1:2011.
- White as standard, special finishes available.
- Switchable, Maintained and non-maintained versions available.

## Specification

- Anti Ligature / Vandal resistant
- IP40
- Tamper Proof Screws
- U.V. Stabilised Opal Diffuser
- High Light Output
- DALI (fluorescent only)
- 28w and 38w 2D lamp
- Colour Options Available
- Self Contained
- Powder Coated Finish

**LED**

**DALI**



IP40



## Options

### Options

/BK	Black base
/MS	Microwave occupancy sensor
/DALI	DALI (fluorescent only)

## Dimensions



## Suitable Applications

- Suitable for incorporation into an emergency lighting system complying with BS5266-1:2011.
- Suitable for use in public and custodial spaces.
- Ideal for areas where higher light levels are required.

## Technical Specification

	Lamp Type	Power Con	Battery	Duration	Weight	Mains Output	Emerg Output
<b>SR28/230</b>	28W 2D	28.7W	-	-	2.57 Kg	2050 Lumens	-
<b>SR28M</b>	28W 2D	29W	3.6V 4Ah	3 Hours	2.92 Kg	1640 Lumens	185 Lumens
<b>SR38M/230</b>	38W 2D	39.7W	-	-	2.57 Kg	3000 Lumens	-
<b>SR38M</b>	38W 2D	39W	4.8V 4Ah	3 Hours	3.14 Kg	2760 Lumens	360 Lumens
<b>SR/LED/230</b>	LED	17W	-	-	3.52 Kg	2100 Lumens	-
<b>SR/LED/EM3</b>	LED	18W	3.6V 4Ah	3 Hours	360 Kg	2100 Lumens	144 Lumens

## Installation Notes

- Diffuser is held in place by a security screw fixed rim, fitting flush to the ceiling.
- Gear tray is easily removable to allow first fix of base.
- All fittings should be tested with a nylon line, if this snags behind the fitting it is deemed "not to be Anti Ligature"

## Materials / Finish

- Comprising of white spun aluminium housing.
- Polycarbonate opal diffuser.
- White as standard, alternative finishes available.

## Catalogue Numbers

<b>SR28/230</b>	28W 2D	28.7W
<b>SR28M</b>	28W 2D	29W
<b>SR38M/230</b>	38W 2D	39.7W
<b>SR38M</b>	38W 2D	39W
<b>SR/LED/230</b>	LED	17W
<b>SR/LED/EM3</b>	LED	18W