

The SR Light is a circular anti ligature vandal resistant luminaire suitable for interior environments.

Comprising of a spun aluminium housing with a polycarbonate opal diffuser, suitable for use on escape routes (850° C Hot-Wire test, defined by ICEL). The diffuser is held in place by a security screw fixed rim, which fits flush to the ceiling. Complying with the requirements of EN60598-2-22 and suitable for incorporation into an emergency lighting system complying with BS5266-1:2011. The SR Light offers an effective solution for harsh environments where both mains and emergency lighting is required. Available in white with special painted finishes to order. Switchable, Maintained and non-maintained versions available.



	Lamp Type	Power Con	Battery	Duration	Weight	Mains Output	Emerg Output
SR28/230	28W 2D	28.7 W	-	-	2.57 Kg	2050 Lumens	-
SR28M	28W 2D	29 W	3.6V 4Ah	3 Hours	2.92 Kg	1640 Lumens	185 Lumens
SR38/230	38W 2D	39.7 W	-	-	2.57 Kg	3000 Lumens	-
SR38M	38W 2D	39 W	4.8V 4Ah	3 Hours	3.14 Kg	2760 Lumens	360 Lumens
SR/LED/230	LED	17 W	-	-	3.52 Kg	2100 Lumens	-
SR/LED/EM3	LED	18 W	3.6V 4Ah	3 Hours	3.60 Kg	2100 Lumens	144 Lumens

## Options

/BK	Black base
/MS	Microwave occupancy sensor
/DALI	DALI (fluorescent only)



- Anti Ligature / Vandal resistant
- IP40
- Tamper Proof Screws
- U.V. Stabilised Opal Diffuser
- High Light Output
- 28w and 38w 2D lamp
- Colour Options Available
- Self Contained
- Powder Coated Finish