

Product Data Sheet

Astro FR-EC Economy Foam

Revision 6 - 20th January 2020



Astro FR-EC Economy Foam

Fire Rated Foam

- Ready to use PU foam in a 750ml can.
- Fire retardant up to 240 minutes.
- Tested in accordance with EN1366-4 : 2006.
- Efficient seal against smoke and gas.
- Excellent adhesion on most construction substrates.
- High bonding strength.
- Very good filling characteristics.
- Excellent stability: no shrink or post expansion.
- Cured foam can be overpainted.



Product Description

Note: This product is fire rated but is not intumescent.

A one-component, self-expanding, ready to use polyurethane foam that uses 'green' propellants, harmless to the ozone layer and without greenhouse gas effects. It has a fire rating of up to 240 minutes (tested according EN1366-4).

- Typical use in linear joint seals.

Properties & Specification

| | |
|-----------------------------------|---------------------------------------------------------|
| Base | Polyurethane |
| Consistency | Stable foam |
| Curing system | Moisture-cure |
| Skin formation - (20°C/65 % R.H.) | Ca 8 minutes |
| Drying time - (20°C/65 % R.H.) | Tackfree after 25min. |
| Curing rate - (20°C/65 % R.H.) | 2 hr for a 30 mm bead |
| Yield | 1000 ml yields 25-40 Lcured foam when extruded in beads |
| Shrink | None |
| Postexpansion | None |
| Colour | Light Red |
| Cellular structure | >70 % closed cells |
| Specific gravity | Ca. 25 kg/m ³ extruded, fully cured |
| Temperature resistance | -40°C to +90°C when cured |

Product Availability

Sold in 750 ml pressurised canisters individually or boxes of 12.

Shelf life is 9 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25

| Product Code | Product Description | Size |
|--------------|--------------------------|-------|
| AFFRECFOAM | Astro FR-EC Economy Foam | 750ml |

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description / sizes
 Typical example:- 10 / AFFRECFOAM / Astro FR-EC Economy Foam / 750ml

>> Tel: [01329 844 500](tel:01329844500) or >> Email: sales@astroflame.com

Application

Shake the aerosol can for at least 20 seconds.

Moisten surfaces with a water sprayer prior to application.

Fill holes and cavities for 65 %, as the foam will expand.

Repeat shaking regularly during application.

If you have to work in layers repeat moistening after each layer.

Fresh foam can be removed using Soudal Foamcleaner or acetone. Cured foam can only be removed mechanically.

Working temperature 5°C to 40°C. (20°C-25°C recommended)

Cured PU-foam must be protected from UV radiation by painting or applying a top layer of sealant (silicone, MS Polymer, acrylic and PU sealant)

Fire Test or Assessment Reports

- Tested in accordance with EN1366-4

Test Results: Test Report 9297C - University of Ghent*

| Wall Thickness | Joint Dimensions | Backing Material | Flame resistance in minutes |
|----------------|-----------------------------|------------------|-------------------------------|
| 200mm | Width: 11mm Depth: 200mm | None | 229 min Fire Rating EI 180 |
| 200mm | Width: 41mm Depth: 200mm | None | 110 min Fire Rating EI 90 |
| 100mm | Width: 30mm Depth: 100mm | None | 50 min Fire Rating EI 45 |
| 100mm | Width: 10mm Depth: 100mm | None | 103 min Fire Rating EI 90 |

Test Results: Test Report 13492 - University of Ghent*

| Wall Thickness | Joint Dimensions | Backing Material | Flame resistance in minutes |
|----------------|-----------------------------|------------------|-------------------------------|
| 200mm | Width: 10mm Depth: 200mm | None | 240 min Fire Rating EI 240 |
| 200mm | Width: 30mm Depth: 200mm | None | 158 min Fire Rating EI 120 |

Installation

Please see installation sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
 or E: sales@astroflame.com

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
 or E: sales@astroflame.com

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME (FIRE SEALS) LTD has no control over the specific application or installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product based on the products limitation of applications and that the product is fit for purpose for their intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROFLAME (FIRE SEALS) LTD, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice. If you are in any doubt as to the suitability of this product for your intended application please contact our technical team on 01329 844500 or email sales@astroflame.com and we will contact you.