



Section 1

FIRE FIGHTING EQUIPMENT

FirePower

POWDER EXTINGUISHERS - Stored Pressure

- Kitemarked to BS EN3
- Multi-purpose application
- Squeeze grip operation
- Corrosion resistant finish
- Protective plastic base*
- Complete with wall bracket

*Excludes 1kg and 2kg models

Type	ABC POWDER SP	ABC POWDER SP	ABC POWDER SP	ABC POWDER SP	ABC POWDER SP	MONNEX POWDER SP
Capacity (kg)	1	2	4	6	9	9
Fire Rating	8A 55B	13A 70B	21A 113B	34A 233B	43A 233B	233B
Height (mm)	340	370	420	503	588	620
Cylinder Dia (mm)	80	112	150	150	170	190
Overall Width (mm)	135	150	293	260	317	310
Filled Weight (kg)	1.67	3.62	6.4	8.94	12.98	14.4
Range of Throw (m)	>2	>2	>6	>6	>7	>7
Duration of Discharge (secs)	9	10	16	20	20	20
Working Pressure (at 20 °C)	15	15	15	15	15	15
Temperature Range (°C)	-30 to +60°C	-30 to +60°C	-30 to +60°C	-30 to +60°C	-30 to +60°C	-20 to +60°C
BS EN3 Approved	✓	✓	✓	✓	✓	✓
Med Approved	NO	NO	NO	✓	✓	NO
Part Number	9315/00	9307/00	9318/00	9319/00	9320/00	9324/00
Model Number	FPP1	FPP2	FPRP4	FPRP6	FPRP9	FPRP9M
Rating Symbol	A B C E	A B C E	A B C E	A B C E	A B C E	A B C E



FirePower

POWDER EXTINGUISHERS - Cartridge Operated

- Kitemarked to BS EN3
- Squeeze grip operation
- Fully reliable
- Controlled discharge
- Multi-purpose application
- Complete with wall bracket
- Strong protective base
- Robust discharge hose



Type	ABC POWDER C/O	ABC POWDER C/O
Capacity (kg)	6	9
Fire Rating	34A 233B	43A 233B
Height (mm)	550	595
Cylinder Dia (mm)	150	170
Overall Width (mm)	280	300
Filled Weight (kg)	10.1	14
Range of Throw (m)	>6	>7
Duration of Discharge (secs)	18	20
Working Pressure (at 20 °C)	15	15
Temperature Range (°C)	-30 to +60°C	-30 to +60°C
BS EN3 Approved	✓	✓
Med Approved	✓	✓
Part Number	9321/00	9322/00
Model Number	FPRP6C	FPRP9C
Rating Symbol	A B C E	A B C E

