



## CERTIFICATE OF DROP TEST

Number: D120616

PRODUCT: Phoenix Fire Resistance Safe

PERFORMANCE SPECIFICATION: We guarantee that all the models stated on the products information table have been drop tested (9.1m) in compliance with KS G 4500.

VALIDITY: This certificate is valid until June 15, 2017.

### Product Information

Model	External dimension (mm)			Internal dimension (mm)			Capacity (ℓ)	Weight (kg)
	height	width	depth	height	width	depth		
phoenix								
FS1271E	300	410	342	220	330	225	16	26
FS1272E, DS2001	412	352	433	320	260	304	25	36
FS1273	514	404	440	410	300	300	36	53
DS2002	600	470	470	480	350	300	50	80
DS2501	635	500	500	515	380	330	64	90
DS2502	816	520	520	676	380	330	84	122
DS2003	770	690	720	590	510	510	153	203
SS1621	960	655	560	780	475	350	129	201
DS2503	1060	655	560	880	475	350	146	209
FS1901, SS1622, DS4621	1160	655	560	980	475	350	162	228
SS1623	1385	775	650	1205	595	440	315	348
FS1902, DS4622	1630	775	650	1450	595	440	379	388
FS1903, DS4623	1685	1126	700	1505	946	490	698	540
FS2242	722	528	675	272	384	505	52	145
FS2244	1406	528	675	272	384	505	52	266
FS2412	730	985	600	266	832	384	84	232
FS2414	1390	985	600	266	832	384	84	392

\* Outside dimension doesn't include the height of plastic feet or plinth.

Busan Korea, June 16, 2012

Bongsoo Han / QC Manager

Younghoon Jung / President