



FIRE FIGHTING EQUIPMENT

Section 1

FirePower**CO₂ EXTINGUISHERS**

- Kitemarked to BS EN3
- Squeeze grip operation
- Corrosion resistant finish
- Harmless to machinery
- 2kg model supplied with frost free horn as standard
- Complete with wall bracket



Type	CO ₂ ALUMINIUM	CO ₂ ALUMINIUM	CO ₂ POLISHED ALUMINIUM	CO ₂ ALUMINIUM NON-MAGNETIC
Capacity (kg)	2	5	2	2
Fire Rating	34B	70B	34B	34B
Height (mm)	490	750	490	490
Cylinder Dia (mm)	117	152	117	117
Overall Width (mm)	180	310	180	180
Filled Weight (kg)	4.91	11.43	4.91	4.91
Range Of Throw (m)	>4	>4	>4	>4
Duration Of Discharge (secs)	8	14	8	8
Working Pressure (at 20 °C)	56	56	56	56
Temperature Range (°C)	-30 to +60°C	-30 to +60°C	-30 to +60°C	-30 to +60°C
BS EN3 Approved	✓	✓	NO	✓
Med Approved	NO	✓	NO	NO
Part Number	9705/00	9706/00	9705/06	9705/65
Model Number	FPC25C	FPC5C	FPC25C	FPC25C
Rating Symbol	B E	B E	B E	B E

**FirePower****SPECIALIST EXTINGUISHER -
Stored Pressure**

- Corrosion resistant high grade valve
- Seize and squeeze for maximum control
- Unique lance applicator designed to allow the powder to fall gently over the fire
- Colour coded zone for easy identification
- Highly effective against metal fires, including Lithium when in the form of powder or swarf



Type	LITHIUM L2 POWDER SP
Capacity (kg)	9
Fire Rating	N/A
Height (mm)	620
Cylinder Dia (mm)	190
Overall Width (mm)	500
Filled Weight (kg)	15.08
Range of Throw (m)	N/A
Duration of Discharge (secs)	30
Working Pressure (at 20 °C)	15
Temperature Range (°C)	-20 to +60°C
BS EN3 Approved	NO
Med Approved	NO
Part Number	9325/00
Model Number	FPRP9L
Rating Symbol	D

