



FirePower



SPECIALIST EXTINGUISHERS

- Corrosion resistant high grade valve
- Squeeze grip operation
- Unique lance applicator designed to allow the powder to fall gently over the fire
- Highly effective against metal fires, which include fires caused by sodium, magnesium and aluminium when in the form of powder or swarf
- The L2 contains powder which is also suitable for fires involving lithium
- CE marked there is no classification in EN3 for D class fires

Type	Lithium L2 Powder S/P	M28 Powder S/P
Capacity (kg)	9	9
Fire rating	N/A	N/A
Height	610	610
Cylinder diameter (mm)	189	189
Overall width (mm)	300	300
Filled weight (kg)	14.56	14.56
Range of throw (m)	N/A	N/A
Duration of discharge (secs)	30	30
Working pressure (at 20°C)	15 bar	15 bar
Temperature range (°C)	-20 to 60	-20 to 60
BS EN3 approved		
MED approved		
Part number	9312/00	9313/00
Model number	FPP9L	FPP9M28



Tel: 0161 654 2222 | Freefax: 0800 281 035
 Website: www.thomas-glover.co.uk | Email: tgsales@tgproducts.co.uk



TG Products Ltd, Parkfield House, Manchester Old Road, Middleton, Manchester, M24 4DY