

Product Data Sheet

Astro FT Sleeve

Revision 4 - 17th January 2020



Astro FT Sleeve

Intumescent Fire Trunk Sleeve

- Fire Trunking Sleeve with a 2 Hour fire rating to BS 476
- Suitable for use through a wide range of fire partition walls and floors.
- Offers excellent acoustic insulation.
- Maintains the thermal insulation of the trunking through the penetration.
- Cost effective solution.
- Fitting only requires access from one side.
- Must protrude by a minimum of 10mm from the wall.



Product Description

The Astroflame range of Astro FT Fire Trunking Sleeves are intended for use where plastic trunking passes through a fire rated wall. The sleeve reinstates the fire rating of the wall which would otherwise be lost.

In the event of a fire, the Astro FT Trunk Sleeve expands with the heat, crushing the trunking and closing off the hole to the fire for at least 2 hours.

The FT Trunk Sleeves are available to fit common sizes of plastic trunking and are suitable for retro fitting with access only required from one side. They are suitable for use with plastic trunking. 25mm thick wall

Product Availability

Astroflame Fire Trunking Sleeves are currently available to fit the following nominal plastic trunking sizes

Product Code	Product Description	Trunking Size	Sleeve Length
AFFTS50	Astro FT Sleeve 50	50x50mm	150mm
AFFTS100	Astro FT Sleeve 100	100x100mm	150mm

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description / Size
Typical example:- 10 / AFFTS100 / Astro FT Sleeve 100 / 50x50x150mm

>> Tel: [01329 844 500](tel:01329844500) or >> Email: sales@astroflame.com

Installation

Please see installation sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
or E: sales@astroflame.com

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
or E: sales@astroflame.com

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME (FIRE SEALS) LTD has no control over the specific application or installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product based on the products limitation of applications and that the product is fit for purpose for their intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROFLAME (FIRE SEALS) LTD, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice. If you are in any doubt as to the suitability of this product for your intended application please contact our technical team on 01329 844500 or email sales@astroflame.com and we will contact you.