



This innovative self contained LED emergency down lighter incorporating a single high output white LED for the illumination of corridors and open areas.


- White polycarbonate flame retardant enclosure.
- High illumination LEDs in a small compact design.
- Exceptionally economical unit - Low energy requirement, long life-span LEDs and batteries.
- Sealed to IP20.
- Device automatically switches to backup operation when mains is interrupted supplying spot light from the battery.
- Complying with the requirements of EN60598-2-22.
- Suitable for incorporation into emergency lighting system complying with BS5266-1:2011.
- Recessed or surface mounted options available.

## Specification



## Dimensions

DIA: 53mm



## Options

### Options

FD004	Fire hood
/SURF	Surface mount enclosure

## Suitable Applications

- Suitable for incorporation into an emergency lighting system complying with BS5266-1:2011.

## Mounting Heights

Mounting Height (M)					
2.5	3.70	9.20	9.20	3.70	OPEN AREAS 0.5 LUX MIN (ANTI-PANIC)
4.0	4.00	10.80	10.80	4.00	
2.5	2.80	7.40	7.40	2.80	ESCAPE ROUTE 1.0 LUX MIN (NORMAL RISK)
4.0	2.60	8.00	8.00	2.60	

## Technical Specification

	Model	Lamp Type	Power Con	Battery	Duration	Weight	Emerg Output
<b>X-DSA</b>	Non Maintained	3W LED	6 VA	4.8V 1.2Ah NiMh	3 Hours	0.12Kg	100 Lumens

## Installation Notes

- Surface mounting option available.
- Ceiling mounting cut out - 46mm
- Ceiling mounting bezzel cut out - 53mm

## Materials / Finish

- White polycarbonate flame-retardant enclosure.