






The Deedlock ANSI Mortice Electric Release is designed for use with Mortice nightlatches fitted to Timber or Metal doors. There are 2 types available:- Standard for most applications or Monitored type which has a snib to monitor the Latchbolt position. Each unit is supplied with both a Short Faceplate (for Metal) and Long Faceplate (for Timber). Easy change from Fail Lock to Fail UnLock operation before installation.


## Features:-

- > Suitable for Hollow Metal/Aluminium or Timber Door Frames
- Supplied with both Short and Long Stainless Steel Faceplates
- Easily Changeable from Fail Locked to Fail UnLocked operation
- Operating Voltage 12v DC (only 250mA Current Draw)
- > Suitable for up to 15mm Latch bolt throw (with 3mm Gap to frame)
- > Long life solenoid tested up to 1 Million operations
- Due to 2,000lbs Jaw strength
- Monitored version available AH111M (monitors Latch bolt position)




Short Faceplate Dimensions (mm)

Product Code	Description	Monitoring
AH111	ANSI Mortice Electric Release 12v DC	-
AH111M	ANSI Mortice Electric Release 12v DC	Latch Bolt




Easily changed from Fail Lock to Fail UnLock operation



Monitoring Snib for Latch bolt position (AH111M only)

Tel: 01704-502801



Long Faceplate Dimensions (mm)