



0910UK

## Smoke Alarm

Designed and developed to satisfy particular UK Fire Brigade requirements, the 0910UK is the ideal smoke alarm combining long-life, peace-of-mind protection with high-specification features and benefits.



[www.staywise.co.uk](http://www.staywise.co.uk)

Kidde is proud to be co-founder and continuing family member of StayWise, the web-based resource promoting safe living through applied learning.



Kidde Safety Europe Ltd

Mathisen Way, Poyle Road, Colnbrook, Berkshire SL3 0HB United Kingdom

Tel: +44 (0) 1753 685148 Fax: +44 (0) 1753 685096 www.kiddesafetyeurope.co.uk

0910UK

## Smoke Alarm

### KEY PRODUCT FEATURES

- Warranted 10 year long-life lithium power cell – for worry free protection.
- Sealed-in power source – reduced user-maintenance. No battery removal or theft problems.
- End-of-life battery warning – gives clear indication of when unit needs replacing at end-of-life.
- Red hush button – easily identified feature to temporarily silence a nuisance alarm. Aids operation of alarm test and hush facilities by the visually impaired.
- Easily adjustable mounting plate – simple for installer to attach plate to wall or ceiling and then connect alarm unit and align for aesthetics.
- Tamper-resist alarm feature – minimises removal of alarm during life-time.
- Separate supplied mounting plate helps protect the alarm circuitry if liquid adhesives are used.
- Self-activation – alarm is activated as soon as attached to mounting plate. This feature ensures users receive full 10 years of alarm life from the time of fitting.
- Deactivation feature – lithium cells can be deactivated after 10 year life-time for safe, environmentally friendly disposal.
- Ionisation technology – quicker at detecting fast-flaming fires.
- Screw and plugs for fitting supplied – self-adhesive tape fitting available on a non warranted basis.
- Alarms boxed individually for ease of transportation

### SPECIFICATIONS

DESCRIPTION	Long life, sealed power source, tamper-proof smoke alarm
UPC NO	0-047871-057238
PART NO	0910UK
WARRANTY (YRS)	10 (for both the alarm and the battery from activation)
TECHNOLOGY	Ionisation
FEATURES	10 year sealed in lithium battery cells, Hush button feature, Tamper-proof alarm, Easily adjustable mounting plate, Self activation, End-of-life battery warning, Environmental 'deactivation' feature
ACCESSORIES	Purpose designed 3M adhesive pads for quick and easy mounting plate installation (fixing screws and plugs supplied)
OPERATION: AC/DC	DC
POWER SOURCE OPERATED	Yes
POWER TYPE	Sealed-in lithium cells (x 3)
PRODUCT WEIGHT	0.20kg
PRODUCT DIMENSIONS	142 x 142 x 40mm (inc. bracket) HxWxD
PERFORMANCE	85 decibels
OPERATING TEMP	40°F (4.4°C) to 100°F (37.8°C)
HUMIDITY RANGE	Up to 85% relative humidity (RH)
INSTALLATION POSITIONS	Wall or Ceiling
INSTRUCTIONS	Owner's manual for homeowner. Separate installer's manual for Fire Brigade fitting use
APPROVALS	BSI Kitemarked BS 5446 pt 1 : 2000, CE

### PACKING SPECIFICATIONS

INDIVIDUAL DIMENSIONS	Each alarm individually packed in white carton 143 x 143 x 50mm HxWxD
WEIGHT	0.27kg incl. Box
OUTER QTY. PER CASE	6
DIMENSIONS	305 x 148 x 148mm HxWxD
WEIGHT	1.75kg