

# Dräger X-am<sup>®</sup> 5100

## Single-gas detector for HF, HCl, H<sub>2</sub>O<sub>2</sub> or hydrazine

For manufacturing petrochemical products, aseptic packing, or handling of rocket fuel: the Dräger X-am 5100 portable single-gas detector guarantees that you use the safest methods possible for handling HF, HCl, H<sub>2</sub>O<sub>2</sub> or hydrazine - thanks to proven Dräger sensor technology and a device design which is perfectly customized to reactive gases.



### YOUR ADVANTAGES AT A GLANCE

- Continuous, precise and reliable measurement
- A special device design with direct gas entry guarantees fast sensor response and precise measurement data by preventing gas adsorption on the device housing
- Lightweight and robust
- Slip-proof and compact design
- Triple alarm: visual (360°), audible (multi-tone), vibration
- Easy to use: two-button operation and user-friendly menus
- Highly resistant to impacts, vibrations and electromagnetic radiation
- Can be operated using replaceable alkaline batteries or a T4 NiMH rechargeable battery, which can be charged right in the device

### TECHNICAL DATA

Dimensions (W x H x D)	48 x 130 x 61 mm; 1.89 x 5.12 x 2.4 inches	
Weight	220 – 250 g; 7.8 - 8.8 oz.	
Ambient conditions	Temperature	-20 to +50 °C; -4 to +122 °F
	Pressure	700 to 1300 mbar; 20.7 to 38.4 inch Hg
	Relative humidity	10 to 95 % RH
Alarms	Visual	360°
	Audible	Multi-tone > 90 dB at 30 cm; 1 ft.
	Vibration	
Ingress Protection	IP 54	
Operating times	~150 h (alkaline battery), ~150 h (NiMH rechargeable battery), or ~180 h (NiMH high capacity rechargeable battery)	
Charging times	< 4 h	
Data logger	Retrievable using an infrared interface > 1000 h at a recording interval of 1 value per minute	
Approvals	ATEX	I M1 Ex ia I Ma II 1G Ex ia IIC T4/T3 Ga -20 °C ≤ Ta ≤ +55/40 °C
	IECEX	Ex ia I Ma Ex ia IIC T4/T3 Ga -20 °C ≤ Ta ≤ +55/40 °C
CE mark	Electromagnetic compatibility Guideline 2004/108/EC Explosion protection – Guideline 94/9/EC	



**Dräger X-am<sup>®</sup> 5100**  
The dependable solution for measuring HF, HCl, H<sub>2</sub>O<sub>2</sub> or hydrazine

## ORDERING INFORMATION

### Dräger X-am 5100

83 22 750

Consisting of: basic device with an integrated data logger, manufacturer's certificate and calibration certificate  
A power pack and sensor are integral elements of a functioning device.

Description	Measuring range	Resolution	Response time (t <sub>90</sub> )	Ordering no.
DrägerSensor XS EC HF/HCl	0 – 30 ppm	0.1 ppm	60 sec.*	68 09 140
DrägerSensor XS EC H <sub>2</sub> O <sub>2</sub>	0 – 20 ppm	0.1 ppm	60 sec.	68 09 170
DrägerSensor XS EC Hydrazin	0 – 3 ppm	0.01 ppm	180 sec.	68 09 190

\*Response time (t<sub>50</sub>)

### Power supply units

NiMH power pack T4 (~150 h operating time)	83 18 704
NiMH power pack T4 high capacity (~180 h operating time)	83 22 244
Alkaline power pack T3/T4 (without alkaline batteries)	83 22 237
Alkaline batteries T4 (2 pcs.) for alkaline power pack 83 22 237 (~150 h operating time)	83 22 239

### Charging accessories

Charging module	83 18 639
Rechargeable battery and charging technology set	83 18 785
Consisting of: NiMH power pack T4, charging module, single charger (worldwide) for 1 charging module	
Rechargeable battery and charging technology set HC	83 22 785
Consisting of: NiMH power pack T4 high capacity, charging module, single charger (worldwide) for 1 charging module	
Charging kit consisting of a charging module and a single charger (worldwide)	83 20 333
Vehicle charging connecting cable 12V/24V for charging module (90 degree connector)	45 52 324
Vehicle charger mounting kit for a Dräger X-am 1/2/5x00 charging module	83 18 779

### Calibration accessories

Calibration adapter	68 06 291
HCl test gas (10 ppm) for sensor 68 09 140	68 12 107
HCl test gas (25 ppm) for sensor 68 09 140	68 12 115
SO <sub>2</sub> test gas (10 ppm) for sensor 68 09 170	68 10 645

### Accessories for measured value datalogger and configuration

Dräger GasVision	83 14 034
Dräger CC-Vision	64 08 515
USB DIRA with USB cable, infrared communication adapter to USB	83 17 409
CC-Vision/DIRA set contains the Dräger CC-Vision, USB cable, IR interface and DIRA adapter charging module X-am 7000	83 18 761
CC-Vision/DIRA professional set contains the Dräger CC-Vision, USB cable, IR interface, DIRA adapter charging module X-am 7000 and barcode reader	83 18 762

### HEADQUARTERS

Dräger Safety AG & Co. KGaA  
Revalstrasse 1  
23560 Lübeck, Germany

[www.draeger.com](http://www.draeger.com)

### SUBSIDIARIES

#### AUSTRALIA

Draeger Safety Pacific Pty. Ltd.  
Axxess Corporate Park  
Unit 99, 45 Gilby Road  
Mt. Waverley Vic 3149  
Tel +61 3 92 65 50 00  
Fax +61 3 92 65 50 95

#### CANADA

Draeger Safety Canada Ltd.  
7555 Danbro Crescent  
Mississauga, Ontario L5N 6P9  
Tel +1 905 821 8988  
Fax +1 905 821 2565

#### P. R. CHINA

Beijing Fortune Draeger Safety  
Equipment Co., Ltd.  
A22 Yu An Rd, B Area,  
Tianzhu Airport Industrial Zone,  
Shunyi District, Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80 05

### FRANCE

Dräger Safety France SAS  
3c route de la Fédération,  
BP 80141  
67025 Strasbourg Cedex 1  
Tel +33 3 88 40 59 29  
Fax +33 3 88 40 76 67

### MEXICO

Draeger Safety S.A. de C.V.  
Av. Peñuelas No. 5 Bodega No. 37  
Fraccionamiento Industrial  
San Pedroto  
Querétaro, Qro México  
Tel +52 442 246-1113  
Fax +52 442 246-1114

### NETHERLANDS

Dräger Safety Nederland B.V.  
Edisonstraat 53  
2700 AH Zoetermeer  
Tel +31 79 344 46 66  
Fax +31 79 344 47 90

### REP. OF SOUTH AFRICA

Dräger South Africa (Pty) Ltd.  
P.O.Box 68601  
Bryanston 2021  
Tel +27 11 465 99 59  
Fax +27 11 465 69 53

### SINGAPORE

Draeger Safety Asia Pte Ltd  
67 Ayer Rajah Crescent  
#06-03  
Singapore 139950  
Tel +65 68 72 92 88  
Fax +65 65 12 19 08

### SPAIN

Dräger Safety Hispania S.A.  
Calle Xaudaró 5  
28034 Madrid  
Tel +34 91 728 34 00  
Fax +34 91 729 48 99

### UNITED KINGDOM

Draeger Safety UK Ltd.  
Blyth Riverside Business  
Park  
Blyth, Northumberland  
NE24 4RG  
Tel +44 1670 352-891  
Fax +44 1670 356-266

### USA

Draeger Safety, Inc.  
101 Technology Drive  
Pittsburgh, PA 15275  
Tel +1 412 787 8383  
Fax +1 412 787 2207