


# Blazex Stored Pressure Fire Extinguisher BXP4 - ABC Dry Powder



## BXP4 ABC Dry Powder



The Blazex ABC 40 powder is a combination of Mono-ammonium phosphate and ammonium sulphate.

On Class A fires the particles fuse and swell to form a barrier which excludes oxygen and prevents re-ignition. On Class B fires the powder interferes with the chemical reactions, thus the flame ceases to exist.

ABC 40 powder is nonconductive and will extinguish Class A (carbonaceous) fires, Class B (flammable liquid) fires and Class C (flammable gas) fires.

## Features

- Manufactured in Great Britain 
- Britannia offer a 5 year quality guarantee against material defects and workmanship
- Colour coded screen
- Brass nickel plated valve
- Pressure indicator gauge (magnetic)
- Additional anti-corrosion treatment available
- Main approvals and certifications as below



EN3



## TECHNICAL SPECIFICATION

Model	Capacity (Kg)	Fire Rating	Full Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Diameter (mm)	Height (mm)
BXP4	4	13A/113B	7.2	-20° to + 60°C	12	17	4	165	415

## SPECIFICATIONS

Operating Pressure @ 20°C	12bar
Test Pressure (PT)	26bar
Maximum Allowable Pressure (PS)	18bar
Minimum Burst Pressure	55bar
Cylinder Material	1.6mm Thick Mild Steel to EN 10111 - DD12
Operating Valve Material	Brass Material - EU grade CuZn40Pbz - EU code CW617N - plus Nickel Plating
Hose and Nozzle	Hose - EPDM Synthetic Rubber
Finish - Red RAL3000 UV Protection	Polyester Powder Paint - Thickness (85 microns avg)
Anti-Corrosion Treatment if Requested	Zinc Coating

## COMPONENT PARTS

Item	Description	Part No.
A	Headcap Assembly	BRHXP4
B	Syphon Tube Assembly	XDT0005
C	Skirt Ring	BRH6010
D	Hose Assembly and Nozzle	IC0450
E	Oetiker Clip	BR0540 & 541
F	Safety Pin	BRH0181
G	Magnetic Pressure Indicator Gauge	P50-GM
-	Pull Tight Seal	BRH0175
-	Wall Bracket	BRH0195
-	4kg ABC 40 Powder refill	PA4

