Britannia P50 Service-Free Fire Extinguishers

Britannia P50 service-free extinguishers offer customers substantial cost savings as they do not require servicing by an extinguisher engineer for 10 years and do not require refilling after 5 years. They are backed by the manufacturer's guarantee, kitemarked by BSI, certified by Apragaz, LPCB and CE marked to BS EN3.

No Maintenance Costs

The Britannia P50 fire extinguishers do not require maintenance by an extinguisher engineer and can be maintained easily by any competent person over its lifespan.

Fully kitemarked and approved

As certified BAFE manufacturers, Britannia produce the P50 extinguishers to the highest standards with British Kitemark, LPCB, Apragaz and CE mark to BS EN 3. In addition the extinguishers are vigorously tested with a crush test and subsequent 12,000 cycle durability test.

10 Year Warranty

The inner core of the P50 is encased in layers of Aramid fibres (used in bullet-proof jackets & modern jets) with only brass and stainless steel components being used, ensuring that P50 extinguishers are 100% corrosion proof and allowing a 10 year manufacturer's guarantee to be provided with every unit.

Free Delivery and Installation Service

Our P50 extinguishers are installed and certified by our BAFE certified extinguisher engineers, free of charge. We will carry out a free site survey at the point of installation to ensure that your premises are fully protected, we will commission your units prior to installing them, supply relevant wall ID signage and provide certificated training for your staff to demonstrate how to visually inspect P50 units.

Key Features:

- Kitemarked to BS EN 3
- No servicing for 10 years
- No refill / discharge after 5 years
- No replacement parts required
- Manufactured in the UK
- Genuine all-inclusive, clear pricing
- 10 year manufacturer's guarantee



EEZE HANDLES. EASE TO STOP.

















www.safelincs.co.uk/britannia

SHOP::: DIRECT



P50 AFFF Foam **Fire Extinguishers**

The P50 foam extinguishers are certified for use on Class A and Class B fires and have been dielectrically tested for safe use on electrical equipment up to 1kV from a distance of 1m, making them far superior to standard foam units on the market.

Operating temperature range

Without Anti Freeze:	+ 5°C	→	+ 60°C
With Anti Freeze:	- 5°C	->	+ 60°C

,∂, A ≫	°€ ₽	\times	\times	\times	4
Class A	Class B	Class C	Class D	Class F	Electrical

Model	Rating	Dimensions
2ltr	8A 55B	410x125mm
6ltr	27A 183B	570x178mm

BRITANNIA

Official Distribution Partner

afelincs

Fire Safety Solutions

FIRF



P50 ABC Powder **Fire Extinguishers**

The powder P50 extinguishers provide an all-round firefighting capability with the ability to tackle Class A, B and C type fires as well as fires involving electrical equipment. Suitable for use outdoors or high risk areas such as car parks, plant rooms and fuel stores.

Operating temperature range

- 20°C + 60°C



Model	Rating	Dimensions	Model
2kg	13A 55B C	410x125mm	2ltr
6kg	43A 183B C	570x178mm	6ltr









N/A

75F



570x178mm

N/A









C 0800 612 6537





P50 Wet Chemical fire extinguishers are the only choice for commercial kitchens with deep fat fryers. Certified to fight Class F type fires these units fight the flames of the fire by smothering the burning fat and then cool it to prevent reignition.

FAT/OIL FIRES

Operating temperature range





A	Class	B Cla	NSS C	Class	DO	ilass F	4 Electri
od	el	Ra	ting		D	imens	ions

ss C	Class	D Cla	iss F	Electrica	I	Class A
ing		Din	nensi	ions		Mod

