

FireAngel

WHT-630T

10 Year Life THERMISTEK Wireless Interlink Heat Alarm

Wi-Safe[®] 2 Wireless Interlink

THERMISTEK[™]



10 year sealed in power pack
removes the need to replace the batteries

Diameter 132mm

Height 60mm

Weight 204g



Common features

- Thermistek predictive technology monitors the rate of temperature increase and alerts you to the danger quicker. Thermistor heat sensing element for accuracy, reliability and stability.
- 10 year sealed for life battery.
- Wirelessly interlink up to 50 Wi-Safe 2 smoke, heat, CO alarms and accessories on a single network.
- Single button provides 'test' and 'silence' functions.
- Optional locking mechanism on installation.
- Class A1 fire detection (54°C - 65°C).
- Locate feature – When a network of alarms goes into alarm pressing the test button on any of the units will silence all but the initiating alarm.
- Heat alarms are for use in places where a smoke detector is not suitable, for example where there are high ambient air temperatures, high humidity or in dusty and dirty environments. eg: garages, lofts and kitchens.



KM607094
BS 5446-2:2003



Technical specification

| | |
|---|---|
| Power | 10 year sealed lithium battery |
| Technology | Thermistek and Wi-Safe 2 |
| Alarm sound level | 85dB at 3m |
| Operation | DC |
| Installation positions | Ceiling |
| Operating temperature | Class A1, 54°C - 65°C |
| Operating humidity | Up to 90% RH% non-condensing |
| Storage temperature | -20°C to 60°C |
| Storage humidity | Up to 93% RH non condensing |
| Warranty | 5 years |
| Master pack quantity | 10 |
| Approvals | Third party certified to BS 5446-2:2003 by BSI |
| Max No. of connected units (network) | 50 units |
| Networking | Multi-directional communication |
| Compatibility | Compatible with all products containing Wi-Safe 2, including use in mixed systems (ie of mains and battery powered products). |
| Independently tested | RF standard ETSI EN 300 220-2 V2.3.2 (2010-02) by TRaC |
| Range | 35m (over 200m in clear air) |
| EAN | 0816317002916 |
| Packaging | Full colour printed cardboard box, in outer boxes of 10 |

FOR FURTHER INFORMATION OR SALES ENQUIRIES:
Tel +44 (0) 2477 717 700 Email sales@sprue.com Website sprue.com

