


Ei166e - Optical Smoke Alarm

Mains Powered 230V with Rechargeable Battery Back-up

Key Features



- ▶ Remote test + control – wired & wireless
- ▶ Integrated piezo-electrical sounder
- ▶ Easi-fit base
- ▶ Insect screen
- ▶ Test/Silence button
- ▶ Memory
- ▶ Low battery indication
- ▶ Hardwire interconnect
- ▶ Wireless interconnect when fitted with Ei100MRF  **RadioLINK+**™ module
- ▶ Kitemarked to BS EN14604:2005
- ▶ 5 year guarantee

Product Description

The Ei166e is an Optical Smoke Alarm with 230V AC mains power supply and rechargeable lithium battery back-up.

The Ei160e family of Alarms have been designed for households and similar residential applications including HMO's (houses in multiple occupation)

The Ei166e is supplied with the Easi-fit base to facilitate quick and simple installation, combined with easy detector head removal and replacement. The Easi-fit base automatically connects both mains power and battery as the detector head slides on.

The Ei166e may operate as a standalone Alarm or may be inter-connected to other Alarms via a wired or wireless system. For  **RadioLINK+**™ interconnection simply plug in the optional  **RadioLINK+**™ module, saving time, mess and disruption in running interconnect cabling.

The Alarm is fitted with a Test / Silence button to facilitate frequent testing of the Alarm and System. The Silence function allows the Alarm / System to be silenced in the case of a false / nuisance alarm, e.g. cooking fumes.

The Ei166e is fitted with a mains "power on" green LED indicator and yellow LED indicator for fault conditions.

The memory feature allows an Alarm that has previously activated to be easily identified.



Technical Specification

Sensor Type:	Optical
Supply Voltage:	230V AC, 50Hz
Battery back-up:	Rechargeable lithium backup battery
Sound Level:	85 dB(A) at 3 meters
Temperature:	Operating - 0 to 40°C Storage - 0 to 35°C (in a dry area)
Humidity Range:	15% to 95% Relative Humidity
Button Test:	Simulates the effect of smoke and checks chamber, electronics and horn
Self-Test:	Smoke Chamber is automatically tested every 40 seconds and unit beeps (without red LED flash) if it is degraded
Insect Screen:	Prevents insects or debris entering chamber (1.00mm mesh size)
Plastic material:	UL94VO flame retardant
Dimensions:	Product - 148mm x 54mm Package - 153mm x 153mm x 62mm
Weight:	336g (Pack +68g)
Guarantee:	5 year (limited) Guarantee
Approvals:	



Kitemarked to BS EN14604:2005

Specifications are subject to change