



## Section 1

## FIRE FIGHTING EQUIPMENT

# FirePower

## WET CHEMICAL - Stored Pressure

- Kitemarked to BS EN3
- Capable of extinguishing a cooking oil or fat fire of up to 75 litres in size
- 13A fire rating for all round safety and embraces the 35kv di-electric test
- EN3 red with official canary yellow colour coding
- User friendly 6 litre size – supplied factory filled
- Wet chemical process seals the surface of burning oil to prevent re-ignition



Type	WET CHEMICAL SPRAY SP
Capacity (ltr)	6
Fire Rating	13A 133B 75F
Height (mm)	662
Cylinder Dia (mm)	170
Overall Width (mm)	310
Filled Weight (kg)	12.13
Range of Throw (m)	>4
Duration of Discharge (secs)	30
Working Pressure (at 20 °C)	7
Temperature Range (°C)	+5 to +60°C
BS EN3 Approved	✓
Med Approved	✓
Part Number	9503/00
Model Number	FPRWC6
Rating Symbol	A B F



# FirePower

## STAINLESS STEEL EXTINGUISHERS - Stored Pressure

- Ideal for environments where hygiene is paramount and when considering architecture
- Highly polished surface finish
- Corrosion resistant construction
- Simple 'squeeze and squeeze' operation
- Controllable discharge assures efficient use of contents and minimises clean-up
- All extinguishers are re-chargeable



Type	AFFF FOAM SP	AFFF FOAM SP	WATER SP	WATER SP
Capacity (ltr)	6	9	6	9
Fire Rating	13A 144B	21A 183B	13A	21A
Height (mm)	500	640	500	640
Cylinder Dia (mm)	180	180	180	180
Overall Width (mm)	300	300	300	300
Filled Weight (kg)	8.63	12.22	8.63	12.22
Range of Throw (m)	>4	>4	>4	>4
Duration of Discharge (secs)	25	40	40	60
Working Pressure (at 20 °C)	15	15	15	15
Temperature Range (°C)	+5 to +60°C	+5 to +60°C	+5 to +60°C	+5 to +60°C
BS EN3 Approved	NO	NO	NO	NO
Med Approved	NO	NO	NO	NO
Part Number	9217/00	9218/00	9905/00	9906/00
Model Number	FPF6S	FPF9S	FPW6S	FPW9S
Rating Symbol	A B	A B	A	A

