

# Norfolk Premier Mobile Fire Extinguisher NRAF135 - BSX Foam



NORFOLK  
RANGE



## NRAF135 BSX Foam



The BSX foam fire extinguisher has excellent firefighting capabilities making it effective on Class A materials fuelled by wood, paper and textiles as well as Class B fires fuelled by paints, solvents, oils and petrochemical products.

The operational temperature range is from +5°C to +60°C.

**Rough terrain double bogey wheels are available.**

## Features

- Manufactured in Great Britain 
- Britannia offer a 10 year quality guarantee against material defects and workmanship
- Colour coded labels
- External CO<sub>2</sub> side cylinder
- Polyester Red (RAL 3000) coating externally and Polymer coating internally gives maximum protection against corrosion
- Main approvals and certifications as below



## TECHNICAL SPECIFICATION

Model	Capacity (Litres)	Fire Rating	Full Weight (Kgs)	Empty Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Width (mm)	Depth (mm)	Height (mm)
NRAF135	135	IVB	224	88	+5° to + 60°C	14.5	200	14	710	770	1230

## SPECIFICATIONS

Side Cylinder	1.0kg CO <sub>2</sub>
Operating Pressure @ 20°C	14.5bar
Test Pressure (PT)	32bar
Maximum Allowable Pressure (PS)	22bar
Minimum Burst Pressure	59.4bar
Safe Operating Distance	5m
Cylinder Material	5mm Thick Mild steel to EN 10111 - DD12
Nut Ring	Zinc Alloy to EN 1774 - ZnA14 (ZL3)
Headblock	Brass C3771
CO <sub>2</sub> Hose	Synthetic rubber reinforced with high tensile wire braid
Paint Finish/Colour	Polyester Red (RAL 3000)
Discharge Hose - 6m (alternative lengths avail on request)	6m Reinforced Rubber

## COMPONENT PARTS

Item	Description	Part No.
A	Body Assembly	NR0165KB
B	1.0KG Side Cylinder with Valve	NCS1000
C	6m Discharge Hose Assembly	HS0010
D	Foam Control Lance/Swivel Connector	HS0410
E	Nut Ring	BRH0105
F	Brass Headblock Assembly	NRH0560
G	CO <sub>2</sub> Hose Assembly	HS0130
H	Solid Rubber Wheels 400mm diameter	WHLS030
I	Washer	WC0140
J	Split pin	WC0150
K	Swivel Connector	NRH0360F
-	Syphon Tube (Internal)	NRH0575
-	Gas Tube (Internal)	NRH580
-	Pull Tight Seal	BRH0175
-	2.03ltr BSX Foam Charge Refill	FOAM250
-	Headcap Spanner	HCS

