



Technical Note

Summary

This Technical Note provides the safety data sheet for the following battery:

<i>Defibtech Product / Description</i>	<i>Defibtech P/N</i>	<i>Manufacturer P/N</i>
B-001002 DDU Series Coin Cell Battery	B-001002	Panasonic BR1225-1HC

This coin cell battery is in both Defibtech DDU-100 and DDU-2000 Series AEDs.

Product Information Sheet

Panasonic Batteries

Panasonic Industrial Company
 A Division Panasonic Corporation of North America
 1701 Golf Road Suite 3-1100
 Rolling Meadows, IL 60008
 Toll Free: 877-726-2228
 Fax: 847-468-5750
 Internet: na.industrial.panasonic.com/products/batteries
 e-mail: oembatteries@us.panasonic.com

Product: Poly-carbonmonofluoride
 (BR Type) Lithium Batteries

Applicable models/sizes: All BR type
 cylindrical and coin batteries, except
 our BR-C.

Revision: January 1, 2016

The batteries referenced herein are exempt articles and are not subject to the OSHA Hazard Communication Standard requirement. This sheet is provided as a service to our customers.

MSDS

Material Safety Data Sheets (MSDS) are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". OSHA has defined "article" as a manufactured item other than a fluid or particle; (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g. minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.

Because all of our batteries are defined as "articles", they are exempt from the requirements of the Hazard Communication Standard; hence a MSDS is not required.

The following components are found in a Panasonic Poly-carbonmonofluoride (BR) Lithium battery:

Cylindrical Cell Components	Material	Formula
Positive Electrode	Poly-carbonmonofluoride	(CF) _n
Negative Electrode	Lithium	Li
Electrolyte	γ-Butyrolactone –Solvent	C ₄ H ₆ O ₂
	1,2 Dimethoxyethane-Solvent	C ₄ H ₁₀ O ₂
	Lithium Tetrafluoroborate-Salt	LiBF ₄
Coin Cell Components	Material	Formula
Positive Electrode	Poly-carbonmonofluoride	(CF) _n
Negative Electrode	Lithium	Li
Electrolyte	γ-Butyrolactone –Solvent	C ₄ H ₆ O ₂
	1,2 Dimethoxyethane-Solvent	C ₄ H ₁₀ O ₂
	Lithium Tetrafluoroborate-Salt	LiBF ₄

DISPOSAL

Lithium batteries are neither specifically listed nor exempted from the Federal Environmental Protection Agency (EPA) hazardous waste regulations as promulgated by the Resource Conservation and Recovery Act (RCRA). The only metal of possible concern in a lithium battery is lithium that is not a listed or characteristic toxic hazardous waste. Waste lithium batteries can be considered a reactive hazardous waste if there is a significant amount of unreacted, or unconsumed lithium remaining in the spent battery. The key to disposing of a lithium battery as a non-hazardous waste is to guarantee that it is fully or mostly discharged. Once it is discharged it can be disposed of as non-hazardous waste.

You can dispose of a fully charged or partially discharged lithium battery as a hazardous waste after they are first neutralized through an approved secondary treatment. The need for a secondary treatment prior to disposal is a requirement of the U.S. Land Ban Restrictions of the Hazardous and Solid Waste Amendments of 1984. A secondary treatment center can only receive these batteries as manifested hazardous waste. The waste code for charged lithium

Notice: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Panasonic Industrial Company makes no warranty expressed or implied.

batteries is D003, reactive. **In either case, button cell batteries contain so little lithium that they never qualify as a reactive hazardous waste. These batteries are safe for disposal in the normal municipal waste stream.**

Disposal of large quantities of undischarged lithium batteries should be performed by permitted, professional disposal firms knowledgeable in Federal, State and local hazardous materials and hazardous waste transportation and disposal requirements. As always, households are exempt from the RCRA hazardous waste guidelines. Check your local area for any recycling options.

TRANSPORTATION

All Panasonic lithium batteries, except for our BR-C, are not subject to the requirements of the Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.

Effective January 1, 2016 all Panasonic lithium batteries can be shipped by air in accordance with International Civil Aviation Organization (ICAO) 2015-2016 edition, Section II or Section 1B or International Air Transport Association (IATA) 57th edition, Section II or Section 1B, Packing Instructions (PI) 968 (Batteries), PI 969 (Batteries, packed with equipment) and PI 970 (Batteries, contained in equipment) as appropriate. Effective January 1, 2015, lithium batteries are banned from Passenger aircraft except when shipped in compliance with Special Provision A201.

All Panasonic lithium batteries are regulated by the International Maritime Organization (IMO), 2014, 37-14 amendment, under Special Provisions 188 and 230.

All Panasonic lithium cells are tested and comply with the UN Model Regulations, Manual of Test and Criteria, Part III, subsection 38.3.

If you build any of our lithium cells into a battery pack, you must also assure that they are tested in accordance with the UN Model Regulations, Manual of Test and Criteria, Part III, subsection 38.3, 5th revised edition, Amendment 2.

The DOT requires that the outside of each package that contains lithium metal batteries, regardless of size or number of batteries, be labeled with the following statement: **"LITHIUM METAL BATTERIES- FORBIDDEN FOR TRANSPORT ABOARD PASSENGER AIRCRAFT"**. The labeling requirement covers shipments via highway, rail, vessel or cargo-only aircraft and covers all shipments inside, into or out of the US. The label must be in contrasting color and the letters must be 12 mm (0.5 in) in height for packages weighing more than 30 Kg and 6 mm (0.25 in) in height for packages weighing less than 30 Kg.

If you plan on transporting any untested prototype battery packs contact your Panasonic Sales Representative for regulatory information.

First Aid

If you get electrolyte in your eyes, flush with water for 15 minutes without rubbing and immediately contact a physician. If you get electrolyte on your skin wash the area immediately with soap and water. If irritation continues, contact a physician. If a battery is ingested, call the National Capital Poison Center (NCPC) at 202-625-3333 (Collect) or your local poison center immediately. Lithium coin batteries lodged in the esophagus should be removed immediately. Leakage, chemical burns and perforation can occur within hours of ingestion.

General Recommendations

CAUTION: Risk of fire, explosion and burns. Do not recharge, crush, heat above 212°F (100°C) or incinerate.

Fire Safety

In case of fire, you can use a Class "D" fire extinguisher or other smothering agent such as Lith-X, copper powder or dry sand. If you use water, use enough to smother the fire. Using an insufficient amount of water will only make the fire worse. Cooling the exterior of the batteries will help prevent rupturing. Burning of these batteries will generate toxic and corrosive lithium hydroxide fumes. Fire fighters should use self-contained breathing apparatus. Detailed information on fighting a lithium metal battery fire can be found in Guide 138 (Substances – Water – Reactive) of the US DOT Emergency Response Guide.

Notice: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation.
Panasonic Industrial Company makes no warranty expressed or implied.
