

Compliance Made Easy

Dorgard Pro

Dorgard Pro is a fire door retainer which holds open fire doors legally, allowing them to automatically close when an alarm is activated.



Overview


Dorgard Pro is a fire door retainer which holds open fire doors legally, allowing them to automatically close when an alarm is activated.

Dorgard Pro is controlled by ProHub, which is directly connected to the fire alarm panel.

Features

- 5 year warranty
- Hassle-free installation
- Connects to any alarm or security panel
- Easily check all units with InSite software*
- Controlled by ProHub, not affected by background noise

Product Dimensions



Overall Height	205mm
Casing Height	150mm
Width	195mm
Depth	45mm
Weight	700g

*Subscription to InSite required, call us for more information

Contact our team for more information

Call: 01273 320650
Email: contact@fireco.uk
Web: www.fireco.uk

Specification Overview

Power	2 x LR14 C-size batteries (included)
Expected battery life	5 years
Colour	Black, white
Activation	Radio signal
Radio frequency	433 MHz
Radio range	Typical internal range 40-50m
Casing	ABS Plastic
Hold open position	Can hold the door at any angle
Maximum door size	Power size 7 (maximum of 160 kg and 1600 mm width)
Audible warning	Warns of door closing on fire or fault
Fire rating	Suitable for up to 60-minute fire doors
Compliant to	EN1155, EN1634, EMC Directive, Radio Equipment Directive, CE Marked
Warranty	5 years
Suitable for	Critical (Category A) installations under BS7273-4 2015
Installation position	Bottom of door
Part number	360-1551 Dorgard Pro Black 956-8278 Dorgard Pro White

Expand the system

Dorgard Pro can be used as part of an expandable system. See below for compatible products

Freedor Pro	338-0604 Freedor Pro Silver Finish 170-2053 Freedor Pro Brass Finish
ProExtender	700-9825 ProExtender Midi 550-7411 ProExtender Maxi
DMS	160-1533 DMS Midi 204-1291 DMS Maxi
ProHub Dorgard Pro is designed to be used in conjunction with the ProHub	198-1593 ProHub Midi 649-4204 ProHub Maxi