## FireAngel.

## SCB10 COMBINATION SMOKE AND CARBON MONOXIDE ALARM (CO)

## Sensor type

Optical (smoke) Electrochemical (CO)

**Battery type** 

10 Year sealed for life battery



- Ideal for bedrooms and living areas.
- One alarm protects against two deadly threats.
  Advanced enticel concing technology reduces
- Advanced optical sensing technology reduces nuisance alarms.
- Advanced electrochemical technology for better CO detection.
- Easy alarm identification with 2 different alarms and indicator lights.
- Equipped with test and "hush" button.
- 30 day low battery warning.
- LED light to indicate power and alarm mode.
- Loud 85 decibel alarm.
- Certified to BS EN14604:2005+AC:2008 Smoke Alarm
- Certified to BS EN50291-1:2010+A1:2012 CO Alarm

Dimensions	134mm (diameter) x 39.4mm (depth)
Supply voltage	3V DC
Battery	10 Year Sealed for life battery
Technology	Optical (smoke) Electrochemical (CO)
Alarm sound level	85dB(A) at 3m (minimum)
Installation positions	Wall / Ceiling
Operating temperature	0°C to +40°C
Operating humidity	Up to 90% RH non-condensing
Storage temperature	-20°C to +50°C
Storage humidity	Up to 93% RH non-condensing
Plastic material	ABS, UL94 VO fire retardant
Warranty	3 years
Weight	200g
Certified to	BS EN 14604:2005 / BS EN 50291-1:2010
Independently tested to	N/A
Maximum number of connected units	N/A
Operating Frequency	N/A
Range	N/A

## **Technical Specification**