

ST-623E-R ESCAPE LIGHT SMOKE ALARM

Sensor type	Thermoptek
Battery type	2 x AA Alkaline Replaceable Batteries (Included)



- Thermoptek Technology - a faster response to slow burning and fast flaming fires.
- Escape Light - an extra bright light to illuminate your escape route.
- Battery Operated.
- Sleep Easy - silence the low battery chirp for 10 hours.
- Alarm Smart Silence - silence your smoke alarm by momentarily pressing the test button, ideal for nuisance alarms.
- Test Button - test the sounder, sensitivity, circuitry and battery.
- Operating Light (RED) - flashes approximately every 45 seconds confirming alarm is powered.
- Low Battery Warning - 'beeps' approximately every 45 seconds for at least 30 days when the battery needs replacing.
- Loud 85 Decibel Piezo Electric Alarm - automatically resets when hazardous condition has passed.
- Suitable for leisure accommodation vehicles (LAV)
- Easy Installation - fixings supplied.



0086-CPR-676744
EN 14604:2005 +AC:2008
Smoke Alarm Device
DoP: SAFLDOP-ST-623E-01



BS EN 14604:2005
+AC:2008
KM 676743

Technical Specification

Dimensions	38.9mm (depth) x 107mm (diameter)	
Supply voltage	3V DC	
Battery	2 x AA Alkaline Replaceable Batteries (Included)	
Technology	Thermoptek	
Alarm sound level	85dB(A) at 1m (minimum)	
Installation positions	Ceiling/ Wall	
Operating temperature	4°C to 38°C	
Operating humidity	30% to 90% RH non-condensing	
Storage temperature	-20°C to +60°C	
Storage humidity	Up to 93% RH non-condensing	
Plastic material	ABS, UL94 VO fire retardant	
Warranty	5 years	
Weight	106g	
Certified to	EN 14604:2005 + AC:2008	
Independently tested to	N/A	
Maximum number of connected units	N/A	
Operating Frequency	N/A	
Range	N/A	