

The 770MBX Smoke Alarm is a mains powered ionisation alarm with 9V alkaline battery back-up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix). The PUSH-FIT base provides spacious room for wiring in premises such as flats where concrete ceilings can be problematic. Top and side entries accommodate for either cable or mini trunking installations.



### Product features:

- 230V mains powered smoke alarm
- 9V alkaline battery back-up
- PUSH-FIT docking base
- Test/ hush button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke & heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS EN 14604: 2005

<b>Model number</b>	770MBX
<b>Description</b>	230V smoke alarm with PUSH-FIT docking base
<b>Technology</b>	Ionisation
<b>Sensitivity</b>	N/A
<b>Alarm sound level</b>	85dB at 3m
<b>Battery type</b>	9V alkaline battery
<b>Operation AC/DC</b>	AC
<b>Installation positions</b>	Ceiling
<b>Operating temperature</b>	+5°C to +38°C
<b>Operating humidity</b>	10% to 85% relative
<b>Storage temperature</b>	+5°C to +38°C
<b>Storage humidity</b>	10% to 85% relative
<b>Warranty</b>	5 years

<b>Dimensions</b>	140mm (diameter) x 53mm (depth)
<b>Unit weight</b>	316g
<b>Pack dimensions</b>	141mm (H) x 141mm (W) x 54mm (D)
<b>Pack weight</b>	318g
<b>Master pack quantity</b>	10
<b>Master pack dimensions</b>	312mm (H) x 153mm (W) x 286mm (D)
<b>Master pack weight</b>	3.18kg
<b>Pack barcode</b>	00029054019820
<b>Outer barcode</b>	10029054019827
<b>Approvals</b>	BS EN 14604: 2005