

Model: 790MBX 230V Mains Powered Heat Alarm

The 790MBX heat alarm is mains powered with 9V alkaline battery back up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix). The PUSH-FIT base provides spacious room for wiring in premises such as flats where concrete ceilings can be problematic. Top and side entries accommodate for either cable or mini trunking installations.



Product features:

- 230V mains powered heat alarm
- 9V alkaline battery back up
- PUSH-FIT docking base (DS700 included)
- Class A2 - Thermistor sensing technology
- Test button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke & heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee

Model number	790MBX
Description	230V heat alarm with PUSH-FIT docking base
Technology	Advanced class A2 thermistor sensing technology
Sensitivity	N/A
Alarm sound level	85db at 3m
Battery type	9V alkaline battery back up
Operation AC/DC	AC
Installation positions	Ceiling
Operating temperature	+5°C to +38°C
Operating humidity	10% to 85% relative
Storage temperature	+5°C to +38°C
Storage humidity	10% to 85% relative
Warranty	5 years

Dimensions	140mm (diameter) x 68mm (depth)
Unit weight	318g
Pack dimensions	141mm (H) x 141mm (W) x 76mm (D)
Pack weight	331g
Master pack quantity	10
Master pack dimensions	312mm (H) x 396mm (W) x 153mm (D)
Master pack weight	3.3kg
Pack barcode	00029054019974
Outer barcode	10029054019971
Approvals	BS 5446-2: 2003