

# UltraFire



## PS1-X ABC

### ABC POWDER FIRE EXTINGUISHER

#### CONSTRUCTION

**BODY** - Single piece, deep drawn aluminium alloy body, externally painted with polyester resin, signal red to RAL 3000.

**VALVE** - Squeeze grip operated with acetal resin body. All external valve parts are either in plastic material or protected against corrosion.

**PROPELLANT** - The propellant is nitrogen. A small percentage of helium is added, to facilitate electronic leak detection.

**EXTINGUISHING AGENT** - ABC multipurpose dry powder. All parts in contact with the extinguisher agent are compatible with the same.

**BRACKET** - Plastic bracket specially designed for vehicle use.

**USE** - For use with A class, B class and C class fires. Safe for use on electrical fires up to 1000 volts.



**ALUMINIUM**

PS1-X ABC is a stored pressure, multi-purpose dry powder fire extinguisher with pressure gauge. Wide operating temperature range  $-30^{\circ}\text{C} + 60^{\circ}\text{C}$ , ensures suitability for use in low-temperature countries. Certified to the Pressure Equipment Directive PED 2014/68/EU, and EN3-7.

100% of the fire extinguishers are checked by an electronic helium leak detection system. Capacity is 1kg.

#### FIRE CLASSES



5

34

✓

#### PRODUCT CERTIFICATION

