

The 690MRL heat alarm is mains powered with rechargeable lithium battery back up that will provide power to the unit in the event of a mains failure. Designed for use in the kitchen, garage or attic, up to 12 compatible smoke and heat alarms can be linked for simultaneous warning.



### Product features:

- 230V mains powered heat alarm
- Rechargeable lithium battery back up
- Advanced class A2 thermistor sensor
- Test/ hush button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke & heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS 5446-2: 2003

<b>Model number</b>	690MRL
<b>Description</b>	230V heat alarm
<b>Technology</b>	Advanced class A2 thermistor sensing technology
<b>Sensitivity</b>	N/A
<b>Alarm sound level</b>	85db at 3m
<b>Battery type</b>	Rechargeable lithium battery back up
<b>Operation AC/DC</b>	AC
<b>Installation positions</b>	Ceiling
<b>Operating temperature</b>	5°C to 38°C
<b>Operating humidity</b>	10% to 85% relative
<b>Storage temperature</b>	5°C to 38°C
<b>Storage humidity</b>	10% to 85% relative
<b>Warranty</b>	5 years

<b>Dimensions</b>	140mm (diameter) x 58mm (depth)
<b>Unit weight</b>	306g
<b>Pack dimensions</b>	138mm (H) x 138mm (W) x 67mm (D)
<b>Pack weight</b>	308g
<b>Master pack quantity</b>	10
<b>Master pack dimensions</b>	306mm (H) x 150mm (W) x 351mm (D)
<b>Master pack weight</b>	3.08kg
<b>Pack barcode</b>	00029054020079
<b>Outer barcode</b>	10029054020076
<b>Approvals</b>	BS 5446-2: 2003