

Model: 770MRL 230V Mains Powered Smoke Alarm

The 770MRL smoke alarm is a mains powered ionisation smoke alarm with rechargeable lithium battery back-up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix). The PUSH-FIT base provides spacious room for wiring in premises such as flats where concrete ceilings can be problematic. Top and side entries accommodate for either cable or mini trunking installations.



Product features:

- 230V mains powered smoke alarm
- Rechargeable lithium battery back up
- PUSH-FIT docking base
- Test/ hush button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke & heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS EN 14604: 2005

Model number	770MRL
Description	230V smoke alarm with PUSH-FIT docking base
Technology	Ionisation
Sensitivity	N/A
Alarm sound level	85dB at 3m
Battery type	Rechargeable lithium battery
Operation AC/DC	AC
Installation positions	Ceiling
Operating temperature	+5°C to +38°C
Operating humidity	10% to 85% relative
Storage temperature	+5°C to +38°C
Storage humidity	10% to 85% relative
Warranty	5 years

Dimensions	140mm (diameter) x 53mm (depth)
Unit weight	262g
Pack dimensions	141mm (H) x 141mm (W) x 54mm (D)
Pack weight	293g
Master pack quantity	10
Master pack dimensions	312mm (H) x 153mm (W) x 321mm (D)
Master pack weight	2.93kg
Pack barcode	00029054019882
Outer barcode	10029054019889
Approvals	BS EN 14604: 2005