

Model: 760MRL 230V Mains Powered Smoke Alarm

The 760MRL smoke alarm is a mains powered optical alarm with rechargeable lithium battery back-up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix). The PUSH-FIT base provides spacious room for wiring in premises such as flats where concrete ceilings can be problematic. Top and side entries accommodate for either cable or mini trunking installations.



Product features:

- 230V mains powered smoke alarm
- Rechargeable lithium battery back up
- PUSH-FIT docking base
- Thermally enhanced optical technology
- Test and alarm pause button
- Low battery warning
- Multi-alarm interlink
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS EN 14604: 2005

Model number	760MRL
Description	230V smoke alarm with PUSH-FIT base
Technology	Thermally enhanced optical technology
Sensitivity	N/A
Alarm sound level	85dB at 3m
Battery type	Rechargeable lithium battery back up
Operation AC/DC	AC
Installation positions	Ceiling
Operating temperature	+5°C to +38°C
Operating humidity	10% to 85% relative
Storage temperature	+5°C to +38°C
Storage humidity	10% to 85% relative
Warranty	5 years

Dimensions	140mm (diameter) x 53mm (depth)
Unit weight	310g
Pack dimensions	141mm (H) x 141mm (W) x 58mm (D)
Pack weight	315g
Master pack quantity	10
Master pack dimensions	312mm (H) x 153mm (W) x 306mm (D)
Master pack weight	3.15kg
Pack barcode	00029054019837
Outer barcode	10029054019834
Approvals	BS EN 14604: 2005