



Save Lives. Streamline Interiors.



Features

CO Alarm Downlight

The Lumi-Plugin Downlight has been designed to integrate a CO alarm.

Downlight Specification

Brand:	Lumi-Plugin
Available Colours:	White or Chrome
IP Rating:	IP65
Material:	Mixed (Metal and Plastic)
Input Voltage to luminaire	16V
Input Voltage to Driver	220V - 240V 50/60Hz
Power Output:	9.5W
Colour Temp:	4000K or 2700K
Light Colour:	Cool White or Warm White
Dimmable:	Yes
Fire Rating:	30/60/90
Luminaires per pack:	1
Product Diameter:	120mm
Product Depth:	70mm
Hours:	50,000
Lumens:	700L
Beam Angle:	60°

Warm or Cool White

Lumi-Plugin's dimmable warm or cool white lights are suitable for both domestic or commercial properties.

Please note: The Lumi-Plugin CO alarms have been developed for domestic use only.

Fire Rated 30/60/90

Lumi-Plugin has passed the BS EN 1365-2:2014 fire test standard in 30/60/90 minutes at the world famous Building Research Establishment (BRE) based in Watford.

Warranty

Lumi-Plugin's CO alarm comes with a 10 year warranty but the downlight comes with a 5 year/50,000 hours warranty.

CO Alarm Specification

Brand:	Lumi-Plugin
Operation AC/DC:	DC
Battery Type:	Powered by a non replaceable 3v CR123A lithium battery 16000mAh
Battery Life:	Minimum 10-year life in normal operating conditions
Sensor Life:	10 years after manufacturing date
Sound:	Audible indicator min. 85 dB @ 3 metre in anechoic chamber
Operating Temperature:	+4°C to +38°C (tested from 0 degrees to 55 degrees)
Operating Humidity:	Up to 90% RH non-condensing