

## Smoke Alarm

Model 29HDRB (single pack)

Model 29HDTRB (twin pack)



### Technical Specifications

Order Code	29HDRB (single pack) / 29HDTRB (twin pack)
Power Supply	9V Battery (Supplied)
Sensor Technology	Optical Sensing Technology
Hush Feature	Yes – allows nuisance alarms to be temporarily silenced
Temperature Range	0°C to 40°C
Humidity Range	Up to 93% relative humidity (RH) non-condensing
LED	Red LED (flash sequence indicates normal, alarm or hush conditions)
Alarm Sound Output	85 decibels at 3m distance
Alarm Indication	Audible and Visual signals
Push to Test Feature	Yes
Approvals	Certified by VDS to EN14604: 2005 / CE certified
Mounting Options	Ceiling mount (bracket included)
Unit Dimensions	104mm x 104mm x 36mm (29HDRB in-packaging) 104mm x 208mm x 36mm (29HDTRB in-packaging) 100mm x 100mm x 33mm (out of packaging)
Unit Weight	175g (packaged weight) 146g (out of packaging)
Life of Alarm	10-year alarm life
Packaging	Individually packaged in cartons
Case Quantity	6 units
Unit Barcode	0 047871 285280 (29HDRB) 0 047871 285297 (29HDTRB)
Outer Barcode	100 47871 285287 (29HDRB) 100 47871 285294 (29HDTRB)
Warranty	3-years