P50 Service-Free Water Mist Fire Extinguishers

IDEAL FOR TACKLING CLASS A & ELECTRICAL FIRE RISKS

P50 Service-Free Water Mist Fire Extinguishers contain only de-ionised water, making them nontoxic and safe for the environment. Suitable for use on Class A (solid combustible) fires and around live electrical equipment, the 2ltr model also features a 5F rating for small, domestic cooking fires. Ideal for homes, offices, schools, hotels, shops, nurseries, rental properties, and HMOs.

P50 service-free fire extinguishers can save you money as they do not require servicing by a 3rd party engineer. Instead, a simple visual inspection can be carried out each year by a member of your team after receiving competency training from Safelincs.

- Suitable for use on Class A (solid combustible) fire risks
- Safe for use on live electrical equipment up to 1000V
- 10 year warranty and 20 year lifespan when refurbished after 10 years
- CE marked and Kitemarked to BS EN3
- Lightweight up to 1.5kg lighter than a steel extinguisher
- UV protection and corrosion proof
- Manufactured in Norfolk, UK
- Fully recyclable at the end of its life
- Super strength composite construction

| Product Code | BEFW2WMAS | BEFW6WMAS | | EXTINGUISHER LTR: WATER MIST E TEST RATING 13A |
|-----------------------|-----------------|-----------------|---|---|
| Capacity | 2ltr | 6ltr | FIREMORID | ROTATE PIN TO BREAK SEAL. REMOVE PIN. UNCLIP HOSE. |
| Extinguisher Ratings | 8A, 5F | 13A | FJU-WAIEK MIDI FIRE EXTINGUISHER 2 LTR: WATER MIST FRE TEST RATING &A - 55 | OPERATE NO CLOSER THAN 2 METRES. AIM AT BASE OF FIRE. |
| Dimensions (HxDia) | 430 x 127mm | 570 x 178mm | 1 ROTATE PIN TO BREAK SEAL. REMOVE PIN. OPERATE NO CLOSER THAN 2 METRES. | RELEASE TO STOP |
| Weight | 2.80kg | 8.50kg | 3 SQUEEZE HANDLES. 3 RELEASE TO STOP | OR USE ON LIVE ELECTRICAL 2 TO 1000V AT A DISTANCE OF 1m |
| Operating Pressure | 12 bar at 20 °C | 12 bar at 20 °C | | <u>felincs</u> 🏘 🇯 |
| Operating Temperature | +5 °C to +60 °C | +5 °C to +60 °C | EQUIPMENT UP TO HODOW AT A DISTANCE OF IN | |
| Discharge Time | 18 sec. | 40 sec. | | 0 |
| Discharge Range | 3m | 4m | | 0 |

For more information, call 0800 612 6537 or email support@safelincs.co.uk







Doc 1579 V1.0