

Hard-wired Alarm Control Switch – Ei1529RC



- Install as part of a hard-wired system to get more control over your Alarms
- Mains powered
- Up to 12 Alarms and Devices can be interconnected
- Three buttons:
 - TEST - Test alarms
 - LOCATE - Identify triggered alarm
 - SILENCE - Silence alarms
- Compatible with Ei2110e, 160e Series Alarms, 140RC Series Alarms and mains powered Carbon Monoxide Alarms

PRODUCT DESCRIPTION

The Ei1529RC Alarm Control switch is designed for use with hardwired smoke/ heat alarms, Carbon Monoxide alarms and devices. It is used to control all the alarms in a system from one convenient place. We highly recommend fitting a control switch if you have multiple smoke and heat alarms on the same system.

The Alarm Control switch increases the flexibility and user friendliness of the alarms by allowing the user to remotely Test, Locate and Silence alarms in the system.


The Test switch allows the user to test the alarms easily, without having to access the alarms on the ceiling. By pressing the Test switch all alarms will sound for a short period.

The Locate switch is primarily used to identify the Alarm sensing Fire/CO. When all the alarms are sounding due to a fire (or nuisance alarm): Press and release the spring loaded Locate Alarm switch. This will silence all the alarms except those sensing Fire/CO.

The Silence switch allows the user to silence all alarms in a system if a false/ nuisance alarm has been identified. By pressing the Silence switch all alarms will stop alarming for a 10-minute period.

The Ei1529RC is supplied complete with its own surface mount pattress and all fixings. It can also be mounted in a standard recessed box (not supplied).

TECHNICAL SPECIFICATION

- Power Supply:** 230V AC, 50Hz
- Temperature:** Operating - 0°C to 40°C
Storage - 0°C to 35°C (in a dry area)
- Humidity range:** 0% to 90% Relative Humidity
- Button functions:** Test - Test Alarms
Locate - Identify triggered alarms
Silence - Silence alarms
- Fixing:** Wall mounting - fixtures supplied
- Dimensions:** Product - 88mm x 88mm x 47mm
Package - 90mm x 90mm x 50mm
- Weight:** 189g (Boxed 208g)
- Warranty:** 5-year (limited) warranty
- Approvals:** 

Specifications are subject to change

Rev2 03/2019 KTS



Company Registration No. 2544399
WEEE Registration No. WEE/AE0109WY
Battery Producer Registration No. 2544399W