



# UltraFire



## Battery Powered Heat Alarm

**Why heat?** Many places within the home are not suitable for even the best smoke alarms. They can be falsely triggered by non-hazardous everyday fumes such as those from cooking, condensation, or even dust. Heat alarms detect a rise in temperature rather than smoke particles and are not prone to these problems.



### Where should heat alarms be used?

Almost any place that is not suited to a smoke alarm. Heat alarms are ideal for installation in kitchens (but not directly over the cooker), garages, boiler rooms, workshops and garden sheds. And if your landing smoke alarm outside your bathroom goes off every time you have a shower, a heat alarm is better than no alarm at all.

TECHNICAL DETAILS	DIMENSIONS (H x DIA)	40 x 102mm
	WEIGHT	0.18kg
	BATTERY TYPE	Replaceable 3V Alkaline (2 x AA)
	SENSOR TYPE	Thermistor
	SOUND OUTPUT	85dB+ at 3 metres
	HEAT SENSITIVITY	54°C – 70°C
	SILENCE TIMEOUT	10 minutes
	DO NOT DISTURB TIMEOUT	8-10 hours
	CERTIFICATION	BS 5446-2: 2003
	SUITABILITY	BS 5839-6 Grade F2
	WARRANTY / LIFESPAN	10 years / 10 years
	PRODUCT CODE	UFUBH1

### What features?

When silenced, the LED will flash silently every 8 seconds for 10 minutes. Low battery chirp can be can be paused at night with Do Not Disturb mode while still monitoring for fire. This alarm comes with fixings and features a large, central Test & Hush button. Backed up by a 10 year warranty.



**Why UltraFire?** Enjoy personal service, quality products and competitive trade pricing when you purchase from UltraFire. With many years of experience supplying a wide range of fire safety products to trade customers worldwide, UltraFire can offer you a reliable service and a range of delivery options to suit.

Contact your UltraFire dedicated Account Manager for quality products at great prices

☎ 0800 612 6537    🖱 [www.ultra-fire.co.uk](http://www.ultra-fire.co.uk)    ✉ [support@ultra-fire.co.uk](mailto:support@ultra-fire.co.uk)